

SpanSet Australia Ltd

150 Old Bathurst Road
Emu Plains
NSW 2750
Australia

Telephone

+61 2 4735 3955

Fax

+61 2 4735 3630






Email







sales@spanset.com.au



Internet

www.spanset.com.au

SRL and Winch Adapters

Brand and Model	Part No	Features	Appearance
SpanSet FPRB15	FPRBB Bracket		
SpanSet IKHRA-30	IKHRAB Bracket		
SpanSet FPMS-20	-		-
SpanSet FPMS-30	-		-
Protecta SRL AD515CG	SPXTIN2152 Adapter	<ul style="list-style-type: none"> - 164kg maximum working load - 1640kg maximum proof load - 31.8cm long x 9.21cm wide x 13.18cm high - Weight 2kg - Steel 44W body and supports - Gr.5 zinc plated steel hardware - Zinc plated steel pin - Nylon covered steel cable lanyard - Black powder paint with metal protection base 	
Miller SRL MR-100G, MR130SB	SPXTIN2177 Adapter	<ul style="list-style-type: none"> - 164kg maximum working load - 1640kg maximum proof load - 32.2cm long x 7.7cm wide x 15.9cm high - Weight 3kg - Steel 44W body and supports - Gr.5 zinc plated steel hardware - Zinc plated steel pin - Nylon covered steel cable lanyard - Black powder paint with metal protection base 	
Miller SRL M52/25	SPXTIN2225 Adapter	<ul style="list-style-type: none"> - 164kg maximum working load - 1640kg maximum proof load - 35.6cm long x 7.8cm wide x 18.1cm high - Weight 2.72kg - Steel 44W body and supports - Gr.5 zinc plated steel hardware - Zinc plated steel pin - Nylon covered steel cable lanyard - Black powder paint with metal protection base 	

Brand and Model	Part No	Features	Appearance
SRL LB287	SPXTIN2226 Adapter	<ul style="list-style-type: none"> – 164kg maximum working load – 1640kg maximum proof load – 18.57cm long x 8.89cm wide x 9.68cm high – Weight 2kg – Steel HSS body – Gr.5 zinc plated steel hardware – Zinc plated steel pin – Nylon covered steel cable lanyard – Black powder paint with metal protection base 	
Miller Man Handler Winch	SPXTIN2191 Adapter	<ul style="list-style-type: none"> – 164kg maximum working load – 1640kg maximum proof load – 18.57cm long x 8.89cm wide x 7.46cm high – Weight 2kg – Steel HSS body – Gr.5 zinc plated steel hardware – Zinc plated steel pin – Nylon covered steel cable lanyard – Black powder paint with metal protection base 	
Ikar SRL 205G-50	SPXTIN2079 Adapter	<ul style="list-style-type: none"> – 164kg maximum working load – 1640kg maximum proof load – 32.7cm long x 10.2cm wide x 17.6cm high – Weight 4kg – Steel 44W body and supports – Gr.5 zinc plated steel hardware – Zinc plated steel pin – Nylon covered steel cable lanyard – Black powder paint with metal protection base 	
Ikar SRL 205G-75	SPXTIN2178 Adapter	<ul style="list-style-type: none"> – 164kg maximum working load – 1640kg maximum proof load – 38.6cm long x 10.5cm wide x 21.4cm high – Weight 4kg – Steel 44W body and supports – Gr.5 zinc plated steel hardware – Zinc plated steel pin – Nylon covered steel cable lanyard – Black powder paint with metal protection base 	
Ikar SRL 205G-100	SPXTIN2231 Adapter	<ul style="list-style-type: none"> – 164kg maximum working load – 1640kg maximum proof load – 42.1cm long x 11.1cm wide x 23.3cm high – Weight 5kg – Steel 44W body and supports – Gr.5 zinc plated steel hardware – Zinc plated steel pin – Nylon covered steel cable lanyard – Black powder paint with metal protection base 	
Sala SRL and Winch	—	—	—
MSA Winch 10011744,50	SPXTIN2151 Adapter	<ul style="list-style-type: none"> – 164kg maximum working load – 1640kg maximum proof load – 37cm long x 10cm wide x 18.5cm high – Weight 2.7kg – Steel 44W body and supports – Gr.5 zinc plated steel hardware – Zinc plated steel pin – Nylon covered steel cable lanyard – Black powder paint with metal protection base 	

Brand and Model	Part No	Features	Appearance
North FP6610/33 (purchased prior to 2012)	SPXTIN2215 Adapter	<ul style="list-style-type: none"> - 164kg maximum working load - 1640kg maximum proof load - 36.8cm long x 7.9cm wide x 8.9cm high - Weight 3kg - Steel HSS body - Gr.5 zinc plated steel hardware - Zinc plated steel pin - Nylon covered steel cable lanyard - Black powder paint with metal protection base 	
North FP6610/15 (purchased prior to 2012)	SPXTIN2191 Adapter	<ul style="list-style-type: none"> - 164kg maximum working load - 1640kg maximum proof load - 18.57cm long x 7.9cm wide x 8.89cm high - Weight 2kg - Steel HSS body - Gr.5 zinc plated steel hardware - Zinc plated steel pin - Nylon covered steel cable lanyard - Black powder paint with metal protection base 	

Training Courses

Height Safety

Working Safely at Height
Working Safely at Heights Refresher
Height Safety Supervisor*
Height Safety Manager*

Rescue

Rescue Systems Operator*
Vertical Rescue*
Tower and Pole Rescue*
Wind Access Rescue Technician*
EWP Emergency Escape
Gotcha Rescue

Confined Space

Confined Space*
Confined Space - Refresher*
Breathing Apparatus*
Confined Space Non-Entry Rescue*

Inspection

Competent Person Practical
Inspection and Record Keeping*



SpanSet Accreditations

ISO 9001:2015 Certified Quality
Management System

ISO 14001:2015 Certified Environment
Management System

OHSAS 18001:2007 Certified Occupational
Health and Safety Management Systems

Australian/New Zealand Standard
4801:2001 certified Occupational Health
and Safety Management Systems

Accredited for compliance with ISO/IEC
17025 - Testing

ASQA Registered Training Organisation
certified to ISO 9001:2008

Certified manufacturer to AS/NZS 1891.1
"Industrial Fall Arrest Systems and Devices"

Certified manufacturer to AS/NZS 1353.1
"Flat Synthetic Webbing Slings"

Certified manufacturer to AS/NZS 4497
"Round Slings—Synthetic Fibre"

www.spanset.com.au

