



SpanSet Australia Ltd

150 Old Bathurst Road
Emu Plains
NSW 2750
Australia

Telephone

+61 2 4735 3955

Fax

+61 2 4735 3630

Email

sales@spanset.com.au

Internet

www.spanset.com.au

A Series Web Slings

SpanSet single ply flat slings are manufactured with reinforced eyes for greater durability

- Wide load bearing surface to minimize damage to fragile loads
- Lightweight for enhanced manual handling safety
- Excellent strength to weight ratio
- Light and flexible for good access in awkward situations
- Certified to AS1353.

A Series Single Ply Flat Webbing Slings Technical Data

Colour / Code	Rated WLL (kg)	1 Width (mm)	2 Thickness (mm)	3 Min Sling Length (mm)	4 Min Eye Length (mm)	Min Pin Diameter (mm)	Min Load Edge Diameter (mm)
A500	500	50	3	845	250	3	9
A1000	1,000	75	4	1240	350	4	12
A2000	2,000	140	4	1750	500	4	12
A3000	3,000	180	4	2400	800	4	12
A4000	4,000	240	4	3000	1000	4	12
A5000	5,000	300	4	3300	1200	4	12

A Series Ordering Codes

Colour / Code	Rated WLL (kg)	1 metre	2 metre	3 metre	4 metre	5 metre	6 metre	8 metre
A500	500	A500-0x1.0	A500-0x2.0	A500-0x3.0	A500-0x4.0	A500-0x5.0	A500-0x6.0	A500-0x8.0
A1000	1,000	A1000-0x1.0	A1000-0x2.0	A1000-0x3.0	A1000-0x4.0	A1000-0x5.0	A1000-0x6.0	A1000-0x8.0
A2000	2,000		A2000-0x2.0	A2000-0x3.0	A2000-0x4.0	A2000-0x5.0	A2000-0x6.0	A2000-0x8.0
A3000	3,000			A3000-0x3.0	A3000-0x4.0	A3000-0x5.0	A3000-0x6.0	A3000-0x8.0
A4000	4,000			A4000-0x3.0	A4000-0x4.0	A4000-0x5.0	A4000-0x6.0	A4000-0x8.0
A5000	5,000			A5000-0x3.0	A5000-0x4.0	A5000-0x5.0	A5000-0x6.0	A5000-0x8.0

Other sizes available on request

secutex® Cut Resistant Sleeves for A Slings

Colour / Code	Secutex Code	Interior Width (mm)	Exterior Width (mm)	Exterior Height (mm)	Weight Per Run (kg/Metre)	Secutex Code	Interior Width (mm)	Exterior Width (mm)	Exterior Height (mm)	Weight Per Run (kg/Metre)	Secutex Code	Interior Width (mm)	Exterior Width (mm)	Exterior Height (mm)	Weight Per Run (kg/Metre)
	Single Sided					Double Sided					Clip-On				
A1000	SF1-50	50	70	22	0.9	SF2-50	50	70	70	1.2	SC-50	50	70	70	1.1
A2000	SF1-75	75	95	22	1.1	SF2-75	75	95	95	1.5	SC-75	75	95	95	1.3
A3000	SF1-100	100	120	22	1.3	SF2-100	100	120	120	1.8	SC-100	100	120	120	1.6
A4000	SF1-140	140	160	22	1.5	SF2-140	140	160	160	2.1	SC-140	140	160	160	1.8
A5000	SF1-150	150	170	22	1.9	SF2-150	150	170	170	2.6	SC-150	150	170	170	2.3



