

ScaffGrip Lifting Slings

Board Sling

User Instructions



MANUFACTURED BY:

SPANSET LTD Telford Way, Middlewich, Cheshire, CW10 0HX

Tel: +44(0)1606 737494 Fax: +44(0)1606 737 264

www.spanset.co.uk

ScaffGrip Lifting Slings—Board Sling

User Instructions

ScaffGrip Lifting Slings are lifting accessories designed to provide a convenient method of lifting scaffold tubes and boards in complete safety. They provide a grip around the scaffold board or tube to prevent the item from slipping or dropping during lifting and avoiding accidents as a consequence.

The ScaffGrip Lifting Slings have a Safe Working Load of 30Kg making them suitable to lift all standard wooden scaffold boards and steel scaffold tubes.



WARNING

The misuse of this equipment could lead to injury or death.
All lifting operations must be properly planned and risk assessed.
Lifting operations should only be performed by a competent person.
This equipment is not designed for lifting or suspension of persons.
Do not exceed the working load limit of this equipment.

LIMITATIONS

ScaffGrip Board lifting slings are designed to provide a convenient method of lifting 38mm timber and plastic scaffolding boards (BS 2482).
The ScaffGrip Board sling should not be used for lifting other materials, goods or scaffold components.
Lifting appliances should only be attached to the yellow rope link as described in the instructions. Do not attach any lifting appliance, equipment or tag line to the metal D link.

ScaffGrip Lifting Slings—Board Sling

User Instructions

Using the ScaffGrip Board Sling

1. Prior to use check the condition of the sling.
2. Open the sling placing it around the scaffold board. Ensure the hook and loop tape is visible on the outside of the sling's webbing.
3. Position the D link on the edge of the scaffold board.
4. Pulling the rope link tight and secure the hook and loop tape together.
5. Pass the rope link through the D link.
6. Secure the lifting appliance to the yellow rope loop.
7. Conduct a trial lift, raising the board so that it is just clear of the floor. Ensure that it is secure and orientated appropriately.
8. Stand clear from underneath the load as it is lifted, lowered or suspended at height.

Inspection and Examination

The ScaffGrip Board sling is a lifting accessory and should be examined at least once every six months by a competent person in accordance with statutory requirements.

Prior to each use the sling should be checked for defects and damage:

Check the label, and that the information is legible.

Check the condition of the plastic heat shrunk cover protecting the label and stitching. It should be intact.

Check the rope and webbing components for signs of:

- Cuts and abrasions.
- Exposed core of the rope.
- Signs of degradation from exposure to chemicals, heat and UV.
- Check the metal D link for and evidence of deformation, cracks, sharp edges or corrosion.

If you are in doubt regarding the suitability or condition of the sling it must be removed from service and examined by a competent person.



Height Safety
Lifting
Load Control
Safety Management

MANUFACTURED BY:

SPANSET LTD Telford Way, Middlewich, Cheshire, CW10 0HX

Tel: +44(0)1606 737494 Fax: +44(0)1606 737 264

www.spanset.co.uk