



SupraPlus-X

Durable and compact design lifting sling with protected label ensures reliable performance and extended service life

Label	Colour	Contact Thickness Under Load [mm]	Contact Width Under Load [mm]	Dimension L1 min [m]	Dimension L1 [m]	WLL kg [kg]	Weight Net [kg]	Weight per Meter [kg/m]
SupraPlus-X 500 0.5m	Olive	4	38	0.5	0.5	500	0.1	0.2
SupraPlus-X 500 0.75m	Olive	4	38	0.5	0.75	500	0.15	0.2
SupraPlus-X 500 1.0m	Olive	4	38	0.5	1	500	0.2	0.2
SupraPlus-X 500 1.5m	Olive	4	38	0.5	1.5	500	0.3	0.2
SupraPlus-X 500 2.0m	Olive	4	38	0.5	2	500	0.4	0.2
SupraPlus-X 500 2.5m (SSCH)	Olive	4	38	0.5	2.5	500	0.4	0.2
SupraPlus-X 500 3.0m (SSCH)	Olive	4	38	0.5	3	500	0.4	0.2
SupraPlus-X 500 5.0m (SSCH)	Olive	4	38	0.5	5	500	0.4	0.2
SupraPlus-X 1000 0.5m	Purple	4	39	0.5	0.5	1000	0.15	0.3
SupraPlus-X 1000 0.75m	Purple	4	39	0.5	0.75	1000	0.22	0.3
SupraPlus-X 1000 1.0m	Purple	4	39	0.5	1	1000	0.3	0.3
SupraPlus-X 1000 1.5m	Purple	4	39	0.5	1.5	1000	0.45	0.3
SupraPlus-X 1000 2.0m	Purple	4	39	0.5	2	1000	0.6	0.3
SupraPlus-X 1000 2.5m	Purple	4	39	0.5	2.5	1000	0.75	0.3
SupraPlus-X 1000 3.0m	Purple	4	39	0.5	3	1000	0.9	0.3
SupraPlus-X 1000 4.0m	Purple	4	39	0.5	4	1000	1.2	0.3
SupraPlus-X 1000 5.0m	Purple	4	39	0.5	5	1000	1.5	0.3
SupraPlus-X 1000 6.0m	Purple	4	39	0.5	6	1000	2.4	0.3



SupraPlus-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Label	Colour	Contact Thickness Under Load [mm]	Contact Width Under Load [mm]	Dimension L1 min [m]	Dimension L1 [m]	WLL kg [kg]	Weight Net [kg]	Weight per Meter [kg/m]
SupraPlus-X 1000 10m (SSCH)	Purple	4	39	0.5	10	1000	4	0.3
SupraPlus-X 2000 0.5m	Green	8	40	0.5	0.5	2000	0.25	0.5
SupraPlus-X 2000 0.75m	Green	8	40	0.5	0.75	2000	0.37	0.5
SupraPlus-X 2000 1.0m	Green	8	40	0.5	1	2000	0.5	0.5
SupraPlus-X 2000 1.5m	Green	8	40	0.5	1.5	2000	0.75	0.5
SupraPlus-X 2000 2.0m	Green	8	40	0.5	2	2000	1	0.5
SupraPlus-X 2000 2.5m	Green	8	40	0.5	2.5	2000	1.25	0.5
SupraPlus-X 2000 3.0m	Green	8	40	0.5	3	2000	1.5	0.5
SupraPlus-X 2000 4.0m	Green	8	40	0.5	4	2000	2	0.5
SupraPlus-X 2000 5.0m	Green	8	40	0.5	5	2000	2.5	0.5
SupraPlus-X 2000 6.0m	Green	8	40	0.5	6	2000	3	0.5
SupraPlus-X 2000 7.0m	Green	8	40	0.5	7	2000	-	0.5
SupraPlus-X 2000 8.0m	Green	8	40	0.5	8	2000	-	0.5
SupraPlus-X 3000 0.5m (SSCH)	Yellow	8	48	0.5	0.5	3000	-	0.6
SupraPlus-X 3000 1.0m	Yellow	8	48	0.5	1	3000	0.6	0.6
SupraPlus-X 3000 1.5m	Yellow	8	48	0.5	1.5	3000	0.9	0.6
SupraPlus-X 3000 2.0m	Yellow	8	48	0.5	2	3000	1.2	0.6
SupraPlus-X 3000 2.5m	Yellow	8	48	0.5	2.5	3000	1.5	0.6
SupraPlus-X 3000 3.0m	Yellow	8	48	0.5	3	3000	1.8	0.6
SupraPlus-X 3000 3.5m (SSCH)	Yellow	8	48	0.5	3.5	3000	2	0.6



SupraPlus-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Label	Colour	Contact Thickness Under Load [mm]	Contact Width Under Load [mm]	Dimension L1 min [m]	Dimension L1 [m]	WLL kg [kg]	Weight Net [kg]	Weight per Meter [kg/m]
SupraPlus-X 3000 4.0m	Yellow	8	48	0.5	4	3000	2.4	0.6
SupraPlus-X 3000 5.0m	Yellow	8	48	0.5	5	3000	3.0	0.6
SupraPlus-X 3000 6.0m	Yellow	8	48	0.5	6	3000	3.6	0.6
SupraPlus-X 3000 7.0m	Yellow	8	48	0.5	7	3000	-	0.6
SupraPlus-X 3000 8.0m	Yellow	8	48	0.5	8	3000	-	0.6
SupraPlus-X 4000 0.5m (SSCH)	Grey	9	54	0.75	0.5	4000	0.4	0.8
SupraPlus-X 4000 1.0m	Grey	9	54	0.75	1	4000	0.8	0.8
SupraPlus-X 4000 1.5m	Grey	9	54	0.75	1.5	4000	1.2	0.8
SupraPlus-X 4000 2.0m	Grey	9	54	0.75	2	4000	1.6	0.8
SupraPlus-X 4000 2.5m	Grey	9	54	0.75	2.5	4000	2	0.8
SupraPlus-X 4000 3.0m	Grey	9	54	0.75	3	4000	2.4	0.8
SupraPlus-X 4000 4.0m	Grey	9	54	0.75	4	4000	3.2	0.8
SupraPlus-X 4000 5.0m	Grey	9	54	0.75	5	4000	4	0.8
SupraPlus-X 4000 6.0m	Grey	9	54	0.75	6	4000	4.8	0.8
SupraPlus-X 4000 7.0m	Grey	9	54	0.75	7	4000	-	0.8
SupraPlus-X 4000 8.0m	Grey	9	54	0.75	8	4000	-	0.8
SupraPlus-X 5000 0.5m	Red	11	59	0.75	0.5	5000	2	1.0
SupraPlus-X 5000 1.0m	Red	11	59	0.75	1	5000	1	1.0
SupraPlus-X 5000 1.5m	Red	11	59	0.75	1.5	5000	1.5	1.0
SupraPlus-X 5000 2.0m	Red	11	59	0.75	2	5000	2	1.0



SupraPlus-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Label	Colour	Contact Thickness Under Load [mm]	Contact Width Under Load [mm]	Dimension L1 min [m]	Dimension L1 [m]	WLL kg [kg]	Weight Net [kg]	Weight per Meter [kg/m]
SupraPlus-X 5000 2.5m	Red	11	59	0.75	2.5	5000	2.5	1.0
SupraPlus-X 5000 3.0m	Red	11	59	0.75	3	5000	3	1.0
SupraPlus-X 5000 3.5m (SSCH)	Red	11	59	0.75	3.5	5000	3.5	1.0
SupraPlus-X 5000 4.0m	Red	11	59	0.75	4	5000	4	1.0
SupraPlus-X 5000 5.0m	Red	11	59	0.75	5	5000	5	1.0
SupraPlus-X 5000 6.0m	Red	11	59	0.75	6	5000	6	1.0
SupraPlus-X 5000 7.0m	Red	11	59	0.75	7	5000	-	1.0
SupraPlus-X 6000 1.0m	Brown	11	68	0.75	1	6000	1.2	1.2
SupraPlus-X 6000 1.5m	Brown	11	68	0.75	1.5	6000	1.8	1.2
SupraPlus-X 6000 2.0m	Brown	11	68	0.75	2	6000	2.4	1.2
SupraPlus-X 6000 2.5m	Brown	11	68	0.75	2.5	6000	3	1.2
SupraPlus-X 6000 3.0m	Brown	11	68	0.75	3	6000	3.6	1.2
SupraPlus-X 6000 4.0m	Brown	11	68	0.75	4	6000	4.8	1.2
SupraPlus-X 6000 5.0m	Brown	11	68	0.75	5	6000	6	1.2
SupraPlus-X 6000 6.0m	Brown	11	68	0.75	6	6000	7.2	1.2
SupraPlus-X 6000 7.0m	Brown	11	68	0.75	7	6000	8.4	1.2
SupraPlus-X 6000 8.0m	Brown	11	68	0.75	8	6000	9.6	1.2
SupraPlus-X 8000 1.0m	Blue	13	74	0.75	1	8000	1.6	1.6
SupraPlus-X 8000 1.5m	Blue	13	74	0.75	1.5	8000	2.4	1.6
SupraPlus-X 8000 2.0m	Blue	13	74	0.75	2	8000	-	1.6



SupraPlus-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

Label	Colour	Contact Thickness Under Load [mm]	Contact Width Under Load [mm]	Dimension L1 min [m]	Dimension L1 [m]	WLL kg [kg]	Weight Net [kg]	Weight per Meter [kg/m]
SupraPlus-X 8000 2.5m	Blue	13	74	0.75	2.5	8000	4	1.6
SupraPlus-X 8000 3.0m	Blue	13	74	0.75	3	8000	4.8	1.6
SupraPlus-X 8000 4.0m	Blue	13	74	0.75	4	8000	6.4	1.6
SupraPlus-X 8000 5.0m	Blue	13	74	0.75	5	8000	8	1.6
SupraPlus-X 8000 6.0m	Blue	13	74	0.75	6	8000	9.6	1.6
SupraPlus-X 8000 7.0m	Blue	13	74	0.75	7	8000	10.6	1.6
SupraPlus-X 8000 8.0m	Blue	13	74	0.75	8	8000	12	1.6

ORDER NUMBERS

Dimension L1	500 kg	1000 kg	2000 kg	3000 kg	4000 kg	5000 kg	6000 kg	8000 kg
0.5	2019184	2019189	2019198	2027101	2027104	2027105	-	-
0.75	2019185	2019190	2019199	-	-	-	-	-
1	2019186	2019191	2019200	2019208	2024570	2024811	2024571	2024816
1.5	2019187	2019192	2019201	2019209	2024669	2024812	2024814	2024817
2	2019188	2019193	2019202	2019210	2019216	2019222	2022135	2022140
2.5	2027097	2019194	2019203	2019211	2019217	2024813	2024815	2024818
3	2027098	2019195	2019204	2019212	2019218	2019223	2022136	2022141
3.5	-	-	-	2027103	-	2027106	-	-
4	-	2019196	2019205	2019213	2019219	2019224	2022137	2022142
5	2027099	2019197	2019206	2019214	2019220	2019225	2022138	2022143
6	-	2024660	2019207	2019215	2019221	2019226	2022139	2022144
7	-	-	2024663	2024665	2024667	2024670	2024672	2024819
8	-	-	2024664	2024666	2024668	-	2024673	2024820
10	-	2027100	-	-	-	-	-	-

■ Main Material	Polyester
■ Temperature Range	- 40 bis + 100°C
■ Safety Factor	7:1
■ Label Protection	Yes
■ Packaging Unit (PU)	pcs



SupraPlus-X

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

■ Packaging Unit (PU) Content 1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length.
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

**SupraPlus-X**

Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom