



### 4-Strang-EXOSET-Kettengehänge

Mit Ovalring und selbstschliessendem Sicherheitshaken CSLH oder mit Lasthaken CSHC

Artikel Name kurz	WLL [kg]	Ketten-Durchmesser	WLL [t]	Öse	L min. [m]	Kette Komponente	Haken-Komponente
4-Exoset CSHC 6	-	6 mm	-	MLA-6-10	0.303	KLX-6-10	CSHC-6-10
4-Exoset CSLH 6	-	6 mm	-	MLA-6-10	0.328	KLX-6-10	CSLH-6-10
4-Exoset CSHC 8	-	8 mm	-	MLA-8-10	0.384	KLX-8-10	CSHC-8-10
4-Exoset CSLH 8	-	8 mm	-	MLA-8-10	0.412	KLX-8-10	CSLH-8-10
4-Exoset CSHC 10	-	10 mm	-	MLA-10-10	0.445	KLX-10-10	CSHC-10-10
4-Exoset CSLH 10	-	10 mm	-	MLA-10-10	0.478	KLX-10-10	CSLH-10-10
4-Exoset CSHC 13	14000	13 mm	14	MLA-13-10	0.593	KLX-13-10	CSHC-13-10
4-Exoset CSLH 13	14000	13 mm	14	MLA-13-10	0.637	KLX-13-10	CSLH-13-10
4-Exoset CSHC 16	-	16 mm	-	MLA-16-10	0.644	KLX-16-10	CSHC-16-10
4-Exoset CSLH 16	-	16 mm	-	MLA-16-10	0.704	KLX-16-10	CSLH-16-10




Artikel Name kurz	WLL t Winkel 0°-45° [t]	WLL t Winkel 45°-60° [t]	WLL kg Winkel 0°-45° [kg]	WLL kg Winkel 45°-60° [kg]	Gewicht für 1m [kg]	Gewicht pro Meter [kg/m]
4-Exoset CSHC 6	2.9	2.1	2900	2100	7	3.6
4-Exoset CSLH 6	2.9	2.1	2900	2100	7	3.6
4-Exoset CSHC 8	5.2	3.7	5200	3700	8.4	6.4
4-Exoset CSLH 8	5.2	3.7	5200	3700	8.4	6.4
4-Exoset CSHC 10	8.4	6	8400	6000	17.2	10
4-Exoset CSLH 10	8.4	6	8400	6000	17.2	10
4-Exoset CSHC 13	14	10	14000	10000	31.5	17.2



Artikel Name kurz	WLL t Winkel 0°- 45° [t]	WLL t Winkel 45°- 60° [t]	WLL kg Winkel 0°- 45° [kg]	WLL kg Winkel 45°- 60° [kg]	Gewicht für 1m [kg]	Gewicht pro Meter [kg/m]
4-Exoset CSLH 13	14	10	14000	10000	31.5	17.2
4-Exoset CSHC 16	21	15	21000	15000	51	26
4-Exoset CSLH 16	21	15	21000	15000	51	26



#### BESTELLNUMMERN[Global Item Number/Local ERP Number SSCH]

WLL t Winkel 0°- 45°	Haken-Komponente	6 mm	8 mm	10 mm	13 mm	16 mm
2.9 t	 CSLH-6-10	2026170 4-CSLH-6	-	-	-	-
2.9 t	 CSHC-6-10	2026165 4-CSHC-6	-	-	-	-
5.2 t	 CSLH-8-10	-	2026171 4-CSLH-8	-	-	-
5.2 t	 CSHC-8-10	-	2026166 4-CSHC-8	-	-	-
8.4 t	 CSLH-10-10	-	-	2026172 4-CSLH-10	-	-
8.4 t	 CSHC-10-10	-	-	2026167 4-CSHC-10	-	-
14 t	 CSLH-13-10	-	-	-	2026173 4-CSLH-13	-
14 t	 CSHC-13-10	-	-	-	2026168 4-CSHC-13	-
21 t	 CSLH-16-10	-	-	-	-	2026174 4-CSLH-16
21 t	 CSHC-16-10	-	-	-	-	2026169 4-CSHC-16

- Normen EN 818-4
- Klasse 100
- Hauptmaterial Stahl
- Farbe Blau
- Temperaturbereich -40° C to + 200° C
- Verpackungseinheit (VPE) Inhalt 1

