

4-Strang Power Bandstruppen Gehänge

Leicht, handlich, materialschonend, flexibel und verrottungsfest



Artikel Name kurz	Öse	Haken-Komponente	WLL t Winkel 0°-45° [t]	WLL t Winkel 45°-60° [t]	L1 min. [m]	Gewicht für 1m [kg]	Gewicht pro Meter [kg/m]
4 leg LBA 0500 ESHC	MLA-8-10	ESHC-6-10	1.05	0.75	0.7	2.38	1
4 leg LBA 0500 ESLH	MLA-8-10	ESLH-6-10	1.05	0.75	0.7	3.38	1
4 leg LBA 1000 ESHC	MLA-8-10	ESHC-8-10	2.1	1.5	0.9	3.3	0.64
4 leg LBA 1000 ESLH	MLA-8-10	ESLH-8-10	2.1	1.5	0.9	4.3	0.64
4 leg LBA 2000 ESHC	MLA-10-10	ESHC-10-10	4.2	3	0.9	5.9	1.28
4 leg LBA 2000 ESLH	MLA-10-10	ESLH-10-10	4.2	3	0.9	7.75	1.28
4 leg LBA 3000 ESHC	MLA-13-10	ESHC-10-10	6.3	4.5	1.20	10.6	2.2
4 leg LBA 3000 ESLH	MLA-13-10	ESLH-10-10	6.3	4.5	1.20	13.2	2.2

Artikel Name kurz	Farbe
4 leg LBA 0500 ESHC	Olivgrün
4 leg LBA 0500 ESLH	Olivgrün
4 leg LBA 1000 ESHC	violett
4 leg LBA 1000 ESLH	violett
4 leg LBA 2000 ESHC	Grün
4 leg LBA 2000 ESLH	Grün
4 leg LBA 3000 ESHC	Gelb
4 leg LBA 3000 ESLH	Gelb





BESTELLNUMMERN[Global Item Number/Local ERP Number SSCH]

Haken-Komponente	1.05 t	2.1 t	4.2 t	6.3 t
 ESLH-6-10	2027927 B4-0500-ESLH	-	-	-
 ESHC-6-10	2027923 B4-0500-ESHC	-	-	-
 ESLH-8-10	-	2027928 B4-1000-ESLH	-	-
 ESHC-8-10	-	2027924 B4-1000-ESHC	-	-
 ESLH-10-10	-	-	2027929 B4-2000-ESLH	2027930 B4-3000-ESLH
 ESHC-10-10	-	-	2027925 B4-2000-ESHC	2027926 B4-3000-ESHC

- Normen EN 1492-1: 2000
- Temperaturbereich -40°C / +100°C
- Verpackungseinheit (VPE) Inhalt 1

