

4-Strang Rundschlingen-Gehänge

Die perfekte Balance



Artikel Name kurz	WLL [kg]	WLL [t]	WLL Einfach gefaltete Anwendung [kg]	WLL Direktanwendung [kg]	L1 [m]	L1 min. [m]	L1 max. [m]
MLS4 2100 EH/C 1m	2100	2.1	2100	1500	1	0.38	10
MLS4 2100 EH/C 2m	2100	2.1	2100	1500	2	0.38	10
MLS4 2100 EH/C 3m	2100	2.1	2100	1500	3	0.38	10
MLS4 2100 EH/C 4m	2100	2.1	2100	1500	4	0.38	10
MLS4 4200 EH/C 1m	4200	4.2	4200	3000	1	0.38	10
MLS4 4200 EH/C 2m	4200	4.2	4200	3000	2	0.38	10
MLS4 4200 EH/C 3m	4200	4.2	4200	3000	3	0.38	10
MLS4 4200 EH/C 4m	4200	4.2	4200	3000	4	0.38	10
MLS4 6300 EH/C 1m	6300	6.3	6300	4500	1	0.38	20
MLS4 6300 EH/C 2m	6300	6.3	6300	4500	2	0.38	20
MLS4 6300 EH/C 3m	6300	6.3	6300	4500	3	0.38	20
MLS4 6300 EH/C 4m	6300	6.3	6300	4500	4	0.38	20
MLS4 8400 EH/C 1m	8400	8.4	8400	6000	1	0.38	20
MLS4 8400 EH/C 2m	8400	8.4	8400	6000	2	0.38	20
MLS4 8400 EH/C 3m	8400	8.4	8400	6000	3	0.38	20
MLS4 8400 EH/C 4m	8400	8.4	8400	6000	4	0.38	20
MLS4 10500 EH/C 1m	10500	10.5	10500	7500	1	0.38	20
MLS4 10500 EH/C 2m	10500	10.5	10500	7500	2	0.38	20
MLS4 10500 EH/C 3m	10500	10.5	10500	7500	3	0.38	20



Artikel Name kurz	WLL [kg]	WLL [t]	WLL Einfach gefaltete Anwendung [kg]	WLL Direktanwendung [kg]	L1 [m]	L1 min. [m]	L1 max. [m]
MLS4 10500 EH/C 4m	10500	10.5	10500	7500	4	0.38	20
MLS4 12600 EH/C 1m	12600	12.6	12600	9000	1	1	20
MLS4 12600 EH/C 2m	12600	12.6	12600	9000	2	1	20
MLS4 12600 EH/C 3m	12600	12.6	12600	9000	3	1	20
MLS4 12600 EH/C 4m	12600	12.6	12600	9000	4	1	20
MLS4 16800 EH/C 1m	16800	16.8	16800	12000	1	1	20
MLS4 16800 EH/C 2m	16800	16.8	16800	12000	2	1	20
MLS4 16800 EH/C 3m	16800	16.8	16800	12000	3	1	20
MLS4 16800 EH/C 4m	16800	16.8	16800	12000	4	1	20
MLS4 21000 EH/C 1m	21000	21	21000	15000	1	1	30
MLS4 21000 EH/C 2m	21000	21	21000	15000	2	1	30
MLS4 21000 EH/C 3m	21000	21	21000	15000	3	1	30
MLS4 21000 EH/C 4m	21000	21	21000	15000	4	1	30
MLS4 31500 EH/C 1m	31500	31.5	31500	22500	1	1	30
MLS4 31500 EH/C 2m	31500	31.5	31500	22500	2	1	30
MLS4 31500 EH/C 3m	31500	31.5	31500	22500	3	1	30
MLS4 31500 EH/C 4m	31500	31.5	31500	22500	4	1	30
MLS4 42000 EH/C 1m	42000	42	42000	30000	1	1	30
MLS4 42000 EH/C 2m	42000	42	42000	30000	2	1	30
MLS4 42000 EH/C 3m	42000	42	42000	30000	3	1	30



Artikel Name kurz	WLL [kg]	WLL [t]	WLL Einfach gefaltete Anwendung [kg]	WLL Direktanwendung [kg]	L1 [m]	L1 min. [m]	L1 max. [m]
MLS4 42000 EH/C 4m	42000	42	42000	30000	4	1	30
MLS4 52500 EH/C 1m	52500	52.5	52500	37000	1	1	30
MLS4 52500 EH/C 2m	52500	52.5	52500	37500	2	1	30
MLS4 52500 EH/C 3m	52500	52.5	52500	37500	3	1	30
MLS4 52500 EH/C 4m	52500	52.5	52500	37500	4	1	30
MLS4 63000 EH/C 1m	63000	63	63000	45000	1	1	30
MLS4 63000 EH/C 2m	63000	63	63000	45000	2	1	30
MLS4 63000 EH/C 3m	63000	63	63000	45000	3	1	30
MLS4 63000 EH/C 4m	63000	63	63000	45000	4	1	30

Artikel Name kurz	Gewicht für 1m [kg]	Gewicht pro Meter [kg/m]
MLS4 2100 EH/C 1m	9.1	1.2
MLS4 2100 EH/C 2m	9.1	1.2
MLS4 2100 EH/C 3m	9.1	1.2
MLS4 2100 EH/C 4m	9.1	1.2
MLS4 4200 EH/C 1m	11.8	2
MLS4 4200 EH/C 2m	11.8	2
MLS4 4200 EH/C 3m	11.8	2
MLS4 4200 EH/C 4m	11.8	2
MLS4 6300 EH/C 1m	18.4	3.2
MLS4 6300 EH/C 2m	18.4	3.2
MLS4 6300 EH/C 3m	18.4	3.2
MLS4 6300 EH/C 4m	18.4	3.2
MLS4 8400 EH/C 1m	27.1	4
MLS4 8400 EH/C 2m	27.1	4
MLS4 8400 EH/C 3m	27.1	4



Artikel Name kurz	Gewicht für 1m [kg]	Gewicht pro Meter [kg/m]
MLS4 8400 EH/C 4m	27.1	4
MLS4 10500 EH/C 1m	32	4.4
MLS4 10500 EH/C 2m	32	4.4
MLS4 10500 EH/C 3m	32	4.4
MLS4 10500 EH/C 4m	32	4.4
MLS4 12600 EH/C 1m	43	5.6
MLS4 12600 EH/C 2m	43	5.6
MLS4 12600 EH/C 3m	43	5.6
MLS4 12600 EH/C 4m	43	5.6
MLS4 16800 EH/C 1m	46.3	7.2
MLS4 16800 EH/C 2m	46.3	7.2
MLS4 16800 EH/C 3m	46.3	7.2
MLS4 16800 EH/C 4m	46.3	7.2
MLS4 21000 EH/C 1m	102	10
MLS4 21000 EH/C 2m	102	10
MLS4 21000 EH/C 3m	102	10
MLS4 21000 EH/C 4m	102	10
MLS4 31500 EH/C 1m	168	14
MLS4 31500 EH/C 2m	168	14
MLS4 31500 EH/C 3m	168	14
MLS4 31500 EH/C 4m	168	14
MLS4 42000 EH/C 1m	260	20
MLS4 42000 EH/C 2m	260	20
MLS4 42000 EH/C 3m	260	20
MLS4 42000 EH/C 4m	260	20
MLS4 52500 EH/C 1m	343	24
MLS4 52500 EH/C 2m	343	24
MLS4 52500 EH/C 3m	343	24
MLS4 52500 EH/C 4m	343	24
MLS4 63000 EH/C 1m	363	32
MLS4 63000 EH/C 2m	363	32
MLS4 63000 EH/C 3m	363	32
MLS4 63000 EH/C 4m	363	32



BESTELLNUMMERN[Global Item Number/Local ERP Number SSDE]

WLL	1 m	2 m	3 m	4 m
2100 kg	2024715 D062885	2002884 D062894	2003354 D007509	2003355 D026155
4200 kg	2024716 D062886	2002886 D062895	2003356 D043621	2003357 D009256
6300 kg	2024717 D062887	2002888 D062896	2003358 D007699	2003359 D013717
8400 kg	2024718 D062888	2002890 D062897	2003360 D020070	2003361 D046097
10500 kg	2024719 D062889	2002892 D062898	2003362 D032007	2003363 D021416
12600 kg	2024720 D062890	2002894 D062899	2003364 D047789	2003365 D005782
16800 kg	2024721 D062891	2002896 D062900	2003366	2003367
21000 kg	2024722 D062892	2002898 D062901	2003368 D025562	2003369 D013718
31500 kg	2024723 D062893	2002900 D062902	2003370 D047792	2003371 D047793
42000 kg	2024724 D016659	2002902 D021718	2003372 D036437	2003373 D047795
52500 kg	2024725 D016660	2002904 D021721	2003374 D047800	2003375 D032865
63000 kg	2024726 D016661	2002906 D021722	2003376 D047802	2003376 D047804

- Normen EN 1492-2
- Hauptmaterial Polyester
- Temperaturbereich -40°C / +100°C
- Verpackungseinheit (VPE) Inhalt 1

