

A-Series 1Ply

Lifting sling manufactured with reinforced eyes for greater durability

Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Minimum Load Edge Radius [mm]
A-Series 250kg 1.5m	250	0.25	1.5	0.62	35	3	9
A-Series 250kg 2.0m	250	0.25	2.0	0.62	35	3	9
A-Series 250kg 2.5m	250	0.25	2.5	0.62	35	3	9
A-Series 250kg 3.0m	250	0.25	3.0	0.62	35	3	9
A-Series 250kg 6.0m	250	0.25	6.0	0.62	35	3	9
A-Series 500kg 1.5m	500	0.5	1.5	0.845	50	3	9
A-Series 500kg 2.0m	500	0.5	2.0	0.845	50	3	9
A-Series 500kg 2.5m	500	0.5	2.5	0.845	50	3	9
A-Series 500kg 3.0m	500	0.5	3.0	0.845	50	3	9
A-Series 500kg 4m	500	0.5	4.0	0.845	50	3	9
A-Series 500kg 5.0m	500	0.5	5.0	0.845	50	3	9
A-Series 500kg 6.0m	500	0.5	6.0	0.845	50	3	9
A-Series 500kg 7.0m	500	0.5	7.0	0.845	50	3	9
A-Series 1000kg 1.5m	1000	1	1.5	1.24	75	4	12
A-Series 1000kg 2.0m	1000	1	2.0	1.24	75	4	12
A-Series 1000kg 2.5m	1000	1	2.5	1.24	75	4	12
A-Series 1000kg 3.0m	1000	1	3.0	1.24	75	4	12
A-Series 1000kg 4.0	1000	1	4.0	1.24	75	4	12
A-Series 1000kg 5.0m	1000	1	5.0	1.24	75	4	12



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Minimum Load Edge Radius [mm]
A-Series 1000kg 6.0m	1000	1	6.0	1.24	75	4	12
A-Series 1000kg 7.0m	1000	1	7.0	1.24	75	4	12
A-Series 1000kg 8.0m	1000	1	8.0	1.24	75	4	12
A-Series 2000kg 1.5m	2000	2	1.5	1.75	140	4	12
A-Series 2000kg 2.0m	2000	2	2.0	1.75	140	4	12
A-Series 2000kg 2.5m	2000	2	2.5	1.75	140	4	12
A-Series 2000kg 3.0m	2000	2	3.0	1.75	140	4	12
A-Series 2000kg 4.0m	2000	2	4.0	1.75	140	4	12
A-Series 2000kg 5.0m	2000	2	5.0	1.75	140	4	12
A-Series 2000kg 6.0m	2000	2	6.0	1.75	140	4	12
A-Series 2000kg 8.0m	2000	2	8.0	1.75	140	4	12
A-Series 3000kg 1.5m	3000	3	1.5	2.4	180	4	12
A-Series 3000kg 2.0m	3000	3	2.0	2.4	180	4	12
A-Series 3000kg 2.5m	3000	3	2.5	2.4	180	4	12
A-Series 3000kg 3.0m	3000	3	3.0	2.4	180	4	12
A-Series 3000kg 4.0m	3000	3	4.0	2.4	180	4	12
A-Series 3000kg 5.0m	3000	3	5.0	2.4	180	4	12
A-Series 3000kg 6.0m	3000	3	6.0	2.4	180	4	12
A-Series 3000kg 7.0m	3000	3	7.0	2.4	180	4	12
A-Series 3000kg 8.0m	3000	3	8.0	2.4	180	4	12



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Minimum Load Edge Radius [mm]
A-Series 4000kg 2.0m	4000	4	2.0	3	240	4	12
A-Series 4000kg 3.0m	4000	4	3.0	3	240	4	12
A-Series 4000kg 4.0m	4000	4	4.0	3	240	4	12
A-Series 4000kg 5.0m	4000	4	5.0	3	240	4	12
A-Series 4000kg 6.0m	4000	4	6.0	3	240	4	12
A-Series 4000kg 8.0m	4000	4	8.0	3	240	4	12
A-Series 5000kg 3.0m	5000	5	3.0	3.3	300	4	12
A-Series 5000kg 4.0m	5000	5	4.0	3.3	300	4	12
A-Series 5000kg 5.0m	5000	5	5.0	3.3	300	4	12
A-Series 5000kg 6.0m	5000	5	6.0	3.3	300	4	12

Item Name short	Colour
A-Series 250kg 1.5m	Olive
A-Series 250kg 2.0m	Olive
A-Series 250kg 2.5m	Olive
A-Series 250kg 3.0m	Olive
A-Series 250kg 6.0m	Olive
A-Series 500kg 1.5m	Olive
A-Series 500kg 2.0m	Olive
A-Series 500kg 2.5m	Olive
A-Series 500kg 3.0m	Olive
A-Series 500kg 4m	Olive
A-Series 500kg 5.0m	Olive



Item Name short	Colour
A-Series 500kg 6.0m	Olive
A-Series 500kg 7.0m	Olive
A-Series 1000kg 1.5m	Purple
A-Series 1000kg 2.0m	Purple
A-Series 1000kg 2.5m	Purple
A-Series 1000kg 3.0m	Purple
A-Series 1000kg 4.0	Purple
A-Series 1000kg 5.0m	Purple
A-Series 1000kg 6.0m	Purple
A-Series 1000kg 7.0m	Purple
A-Series 1000kg 8.0m	Purple
A-Series 2000kg 1.5m	Green
A-Series 2000kg 2.0m	Green
A-Series 2000kg 2.5m	Green
A-Series 2000kg 3.0m	Green
A-Series 2000kg 4.0m	Green
A-Series 2000kg 5.0m	Green
A-Series 2000kg 6.0m	Green
A-Series 2000kg 8.0m	Green
A-Series 3000kg 1.5m	Yellow
A-Series 3000kg 2.0m	Yellow
A-Series 3000kg 2.5m	Yellow
A-Series 3000kg 3.0m	Yellow
A-Series 3000kg 4.0m	Yellow
A-Series 3000kg 5.0m	Yellow
A-Series 3000kg 6.0m	Yellow
A-Series 3000kg 7.0m	Yellow



Item Name short	Colour
A-Series 3000kg 8.0m	Yellow
A-Series 4000kg 2.0m	Grey
A-Series 4000kg 3.0m	Grey
A-Series 4000kg 4.0m	Grey
A-Series 4000kg 5.0m	Grey
A-Series 4000kg 6.0m	Grey
A-Series 4000kg 8.0m	Grey
A-Series 5000kg 3.0m	Red
A-Series 5000kg 4.0m	Red
A-Series 5000kg 5.0m	Red
A-Series 5000kg 6.0m	Red

ORDER NUMBERS[Global Item Number/Local ERP Number SSAU]

Dimension L1	250 kg	500 kg	1000 kg	2000 kg	3000 kg	4000 kg	5000 kg
1.5 m	2029073 A0250-0x1.5	2029078 A0500-0x1.5	2029086 A1000-0x1.5	2029095 A2000-0x1.5	2029103 A3000-0x1.5	-	-
2.0 m	2029074 A0250-0x2.0	2029079 A0500-0x2.0	2029087 A1000-0x2.0	2029096 A2000-0x2.0	2029104 A3000-0x2.0	2029113 A4000-0x2.0	-
2.5 m	2029075 A0250-0x2.5	2029080 A0500-0x2.5	2029088 A1000-0x2.5	2029097 A2000-0x2.5	2029105 A3000-0x2.5	-	-
3.0 m	2029076 A0250-0x3.0	2029081 A0500-0x3.0	2029089 A1000-0x3.0	2029098 A2000-0x3.0	2029106 A3000-0x3.0	2029114 A4000-0x3.0	2029119 A5000-0x3.0
4.0 m	-	2029082 A0500-0x4.0	2029090 A1000-0x4.0	2029099 A2000-0x4.0	2029107 A3000-0x4.0	2029115 A4000-0x4.0	2029120 A5000-0x4.0
5.0 m	-	2029083 A0500-0x5.0	2029091 A1000-0x5.0	2029100 A2000-0x5.0	2029108 A3000-0x5.0	2029116 A4000-0x5.0	2029121 A5000-0x5.0
6.0 m	2029077 A0250-0x6.0	2029084 A0500-0x6.0	2029092 A1000-0x6.0	2029101 A2000-0x6.0	2029109 A3000-0x6.0	2029117 A4000-0x6.0	2029122 A5000-0x6.0
7.0 m	-	2029085 A0500-0x7.0	2029093 A1000-0x7.0	-	2029110 A3000-0x7.0	-	-
8.0 m	-	-	2029094 A1000-0x8.0	2029102 A2000-0x8.0	2029111 A3000-0x8.0	2029118 A4000-0x8.0	-

■ Standards	AS 1353.1
■ Main Material	Polyester
■ Temperature Range	-40°C / +100°C

SpanSet Australia Ltd
150 Old Bathurst Road
Emu Plains NSW 2750
Australia
+61 (02) 4735 3955
sales@spanset.com.au
www.spanset.com.au



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Australia Ltd

**SpanSet
Certified
Safety**

■ Number of layers	1
■ Label Protection	Yes
■ Packaging Unit (PU) Content	1

