



ABS 2500daN 50mm

Robust and durable ratchet with progressive release, for safe release of tension and no load tipping

Item Name short	Lashing Type	Lashing Capacity [daN]	L2 [m]	L3 [m]	Lashing End Fitting Component
ABS LC2500/50 0.5m 7.5m DJH	Two-piece	2500	0.5	7.5	DJH-50
ABS LC2500/50 0.5m 7.5m DJHS	Two-piece	2500	0.5	7.5	DJHS-50
ABS LC2500/50 0.5m 7.5m RH	Two-piece	2500	0.5	7.5	RH-50
ABS LC2500/50/STF350 2pc 8m SHD	Two-piece	2500	0.5	7.5	SHD-50
ABS LC5000/50 1pc 8m	One-piece	5000	-	-	No



ORDER NUMBERS[Global Item Number/Local ERP Number SSNL]

Length

	No	DJH-50	DJHS-50	RH-50	SHD-50
8 m	2004038	2004040	2004481	2004482	2004039

■ Norms	EN 12195-2: 2001
■ Surface Coating	Epoxy
■ Webbing Material	Polyester, thermofixed and low-stretch <4%
■ Colour	Blue
■ Webbing Width B	50 mm
■ Standard Tension Force	500 daN
■ Anti Belt Slip (ABS)	Yes
■ Tension Force Indicator (TFI)	Yes
■ Label Protection	Yes
■ Handle Type	Standard
■ Packaging Unit (PU) Content	1

SpanSet Nederland B.V.
Plaza 10A 4782 SK
Moerdijk Nederland
Tel.: +31 (0) 168 38 68 00
info@spanset.nl
www.spanset.nl



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed via electronic systems without the written permission of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Nederland B.V.

**SpanSet
Certified
Safety**