



ABS 2500daN 50mm

Robust and durable ratchet with progressive release, for safe release of tension and no load tipping

Item Name short	Lashing Type	Length [m]	Lashing Capacity [daN]	L1 [m]	L2 [m]	L3 [m]	Lashing End Fitting Component
ABS LC2500/50/STF350 2pc 6m DJH	Two-piece	6	2500	6	0.5	5.5	DJH-50
ABS LC2500/50 0.5m 7.5m DJH	Two-piece	8	2500	8	0.5	7.5	DJH-50
ABS LC2500/50 0.5m 7.5m DJHS	Two-piece	8	2500	8	0.5	7.5	DJHS-50
ABS LC2500/50 0.5m 7.5m RH	Two-piece	8	2500	8	0.5	7.5	RH-50
ABS LC5000/50 1pc 8m	One-piece	8	5000	8	-	-	No
ABS LC2500/50 0.5m 9.5m DJH	Two-piece	10	2500	10	0.5	9.5	DJH-50

ORDER NUMBERS[Global Item Number/Local ERP Number SSUK]

Length	No	DJH-50	DJHS-50	RH-50
6 m	-	2020326	-	-
8 m	2004038	2004040	2004481 20020-2-01228SL-8MTFI	2004482
10 m	-	2020327	-	-

■ Norms	EN 12195-2: 2001
■ Surface Coating	Epoxy
■ Webbing Material	Polyester, thermofixed and low-stretch <4%
■ Colour	Blue
■ Webbing Width B	50 mm
■ Standard Tension Force	500 daN
■ Anti Belt Slip (ABS)	Yes
■ Tension Force Indicator (TFI)	Yes
■ Label Protection	Yes
■ Handle Type	Standard
■ Packaging Unit (PU) Content	1

SpanSet (UK) Limited
Telford Way
Middlewich Cheshire
CW10 0HX United Kingdom
+44 (0) 1606 737494
info@spanset.co.uk
www.spanset.co.uk



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

SpanSet
Certified
Safety

