



ABS 5000daN 50mm

Transport heavy loads safely with progressive release, for safe release of tension and no load tipping

Item Name short	Surface Coating	Lashing End Fitting Component	Weight Net [kg]
ABS LC5000/50 carlash 4m DD	no	DD-50	3.9
ABS LC5000/50 carlash 4m DD b	Epoxy	DD-50	3.9
ABS LC5000/50 carlash 4m DH b	Epoxy	DH-50	5.4
ABS LC5000/50 carlash 4m DH	Chromated	DH-50	5.4

ORDER NUMBERS[Global Item Number/Local ERP Number SSDE]

Lashing End Fitting Component	no	Chromated	Epoxy
 DD-50	2003502 D003603	-	2004016 D003610
 DH-50	-	2004013 D003605	2004017 D003612

■ Norms	EN 12195-2: 2001
■ Webbing Material	Polyester, thermofixed and low-stretch <4%
■ Colour	Blue
■ Webbing Width B	50 mm
■ Standard Tension Force	500 daN
■ Lashing Capacity	5'000 daN
■ Anti Belt Slip (ABS)	Yes
■ Tension Force Indicator (TFI)	No
■ Label Protection	Yes
■ Handle Type	Standard
■ Packaging Unit (PU) Content	1

SpanSet GmbH & Co. KG
Jülicher Straße 49-51
52531 Übach-Palenberg
Deutschland
+49 (0) 2451 4831-0
info@spanset.de
www.spanset.com



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written authorisation of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. DB040719 © SpanSet GmbH & Co. KG - Germany

**SpanSet
Certified
Safety**