

Anschlagpunkt "DSR"

Anschlagwirbel mit Dreh- und Schwenkfunktion DSR



Artikel Name kurz	WLL kg Winkel 0° [kg]	WLL t Winkel 0° [t]	WLL kg Winkel 90° [kg]	WLL t Winkel 90° [t]	A [mm]	B [mm]	C [mm]
DSR-M6	200	0.2	200	0.2	33	30	30
DSR-M8	500	0.5	500	0.5	33	30	30
DSR-M10	900	0.9	900	0.9	33	30	30
DSR-M12	1500	1.5	1500	1.5	33	30	30
DSR-M16	2300	2.3	2300	2.3	45	40	45
DSR-M20	2500	2.5	2500	2.5	45	40	45
DSR-M24	5500	5.5	5500	5.5	62	55	60
DSR-M30	6300	6.3	6300	6.3	62	55	60

Artikel Name kurz	D [mm]	E [mm]	F [mm]	G [mm]	H [mm]	M [mm]	Nettogewicht kg [kg]
DSR-M6	38	27	14	53	9.5	6	0.3
DSR-M8	38	27	14	53	9.5	8	0.3
DSR-M10	38	27	14	53	9.5	10	0.3
DSR-M12	38	27	14	53	9.5	12	0.3
DSR-M16	53	38	17	76	13	16	0.9
DSR-M20	53	38	17	76	13	20	0.9
DSR-M24	83	55	25	115	19	24	2.6
DSR-M30	83	55	25	115	19	30	2.7



BESTELLNUMMERN[Global Item Number/Local ERP Number SSCH]

WLL t Winkel 0°	DSR-M6	DSR-M8	DSR-M10	DSR-M12	DSR-M16	DSR-M20	DSR-M24	DSR-M30
0.2 t	2027664 DSR-M6(0.4)UP	-	-	-	-	-	-	-
0.5 t	-	2027665 DSR-M8(1.0)UP	-	-	-	-	-	-
0.9 t	-	-	2027666 DSR-M10(1.5)UP	-	-	-	-	-
1.5 t	-	-	-	2027667 DSR-M12(1.5)UP	-	-	-	-
2.3 t	-	-	-	-	2027668 DSR-M16(2.8)UP	-	-	-
2.5 t	-	-	-	-	-	2027669 DSR-M20(2.8)UP	-	-
5.5 t	-	-	-	-	-	-	2027670 DSR-M24(6.5)UP	-
6.3 t	-	-	-	-	-	-	-	2028150 DSR-M30(6.3)UP

- Normen ISO 12100 EN 1677-1
- Hauptmaterial Stahl
- Farbe Rot
- Temperaturbereich -40°C bis +100°C
- Verpackungseinheit (VPE) Inhalt 1

