


Blue Pin Schäkel, geschweißt und mit Kragenbolzen

Geschweißter Schäkel



Artikel Name kurz	WLL [kg]	WLL [t]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]
BluePin B SCP 1t	1000	1	16.8	11	35.7	9.7	26.2
BluePin B SCP 1.5t	1500	1.5	19	13	42.2	11.2	29.5
BluePin B SCP 2t	2000	2	20.6	16	47.2	12.7	33.1
BluePin B SCP 3.25t	3250	3.25	27	20	60	16	42
BluePin B SCP 4.75t	4750	4.75	31.8	22	71	19	51
BluePin B SCP 6.5t	6500	6.5	36.6	27	84	22	58
BluePin B SCP 8.5t	8500	8.5	43	28.5	95	25	68
BluePin B SCP 9.5t	9500	9.5	46	33	108	28	74
BluePin B SCP 12t	12000	12	51.5	36	119	32	82
BluePin B SCP 13.5t	13500	13.5	57	38	131	35	89
BluePin B SCP 17t	17000	17	60.5	42	148	38	98
BluePin B SCP 25t	25000	25	73	51	177	45	127
BluePin B SCP 35t	35000	35	82.5	57	197	51	146

Artikel Name kurz	F [mm]	H [mm]	M [mm]	Nettogewicht kg [kg]
BluePin B SCP 1t	23.1	62.2	11	0.15
BluePin B SCP 1.5t	26.9	73.9	13	0.24
BluePin B SCP 2t	30.2	83.5	16	0.4
BluePin B SCP 3.25t	39	106	20	0.60
BluePin B SCP 4.75t	47	125	22	1.0
BluePin B SCP 6.5t	54	147	27	1.50
BluePin B SCP 8.5t	60	166	30	2.35
BluePin B SCP 9.5t	66	185	33	3.20
BluePin B SCP 12t	76	208	36	4.3
BluePin B SCP 13.5t	84	228	-	6.36
BluePin B SCP 17t	92	254	42	7.40
BluePin B SCP 25t	109	303	51	12.8
BluePin B SCP 35t	127	-	57	18.2



BESTELLNUMMERN[Global Item Number/Local ERP Number SSDE]

WLL	BluePin B SCP 1t	BluePin B SCP 1.5t	BluePin B SCP 2t	BluePin B SCP 3.25t	BluePin B SCP 4.75t	BluePin B SCP 6.5t	BluePin B SCP 8.5t	BluePin B SCP 9.5t	BluePin B SCP 12t	BluePin B SCP 13.5t	BluePin B SCP 17t
1 t	2000772	-	-	-	-	-	-	-	-	-	-
1.5 t	-	2000773	-	-	-	-	-	-	-	-	-
2 t	-	-	1058249 D058249	-	-	-	-	-	-	-	-
3.25 t	-	-	-	1058250 D058250	-	-	-	-	-	-	-
4.75 t	-	-	-	-	2000774	-	-	-	-	-	-
6.5 t	-	-	-	-	-	1058269 D058269	-	-	-	-	-
8.5 t	-	-	-	-	-	-	1051713 D058270	-	-	-	-
9.5 t	-	-	-	-	-	-	-	2000776	-	-	-
12 t	-	-	-	-	-	-	-	-	2000777	-	-
13.5 t	-	-	-	-	-	-	-	-	-	1058273 D058273	-
17 t	-	-	-	-	-	-	-	-	-	-	2000779
25 t	-	-	-	-	-	-	-	-	-	-	-
35 t	-	-	-	-	-	-	-	-	-	-	-

WLL	BluePin B SCP 25t	BluePin B SCP 35t
1 t	-	-
1.5 t	-	-
2 t	-	-
3.25 t	-	-
4.75 t	-	-
6.5 t	-	-
8.5 t	-	-
9.5 t	-	-
12 t	-	-
13.5 t	-	-
17 t	-	-
25 t	2000780 D058275	-
35 t	-	2000781 D040585



■ Normen	EN 13889
■ Klasse	50
■ Hauptmaterial	Stahl
■ Temperaturbereich	0° C to + 200° C
■ Verpackungseinheit (VPE) Inhalt	1

