


Catena Exoset G100

Più leggeri e facili da utilizzare

Nome articolo breve	WLL kg [kg]	Diametro catena	WLL ton [t]	D [mm]	E [mm]	H [mm]	Peso netto [kg]
KLX-6-10	1400	6 mm	1.4	6	18	7.8	0.9
KLX-8-10	2500	8 mm	2.5	8	24	10.9	1.6
KLX-10-10	4000	10 mm	4	10	30	13	2.5
KLX-13-10	6700	13 mm	6.7	13	39	17.5	4.3
KLX-16-10	10000	16 mm	10	16	48	20.8	6.5



ARTICOLO[Global Item Number/Local ERP Number SSIT]

Diametro catena	KLX-6-10	KLX-8-10	KLX-10-10	KLX-13-10	KLX-16-10
6 mm	2000795	-	-	-	-
8 mm	-	2000796	-	-	-
10 mm	-	-	2000797	-	-
13 mm	-	-	-	2000798	-
16 mm	-	-	-	-	2000799

■ Norme	EN 818 ASTM 973
■ Grado	100
■ Materiale principale	Acciaio
■ Colore	Blu
■ Intervallo di temperatura	-40°C / 200°C
■ Intervallo di temperatura	-40°F / 120°F
■ Packaging Unit (PU) Contenuto	1

