


Chaîne de levage EXOSET®

Capacité de charge supérieure de 25% à celle des produits de grade 8.

Nom court de l'article	WLL [kg]	Diamètre de la chaîne	WLL [t]	D [mm]	E [mm]	H [mm]	Poids net [kg]
KLX-6-10	1400	6 mm	1.4	6	18	7.8	0.9
KLX-8-10	2500	8 mm	2.5	8	24	10.9	1.6
KLX-10-10	4000	10 mm	4	10	30	13	2.5
KLX-13-10	6700	13 mm	6.7	13	39	17.5	4.3
KLX-16-10	10000	16 mm	10	16	48	20.8	6.5



NUMÉROS DE COMMANDE[Global Item Number/Local ERP Number SSFR]

Diamètre de la chaîne	KLX-6-10	KLX-8-10	KLX-10-10	KLX-13-10	KLX-16-10
6 mm	2000795	-	-	-	-
8 mm	-	2000796	-	-	-
10 mm	-	-	2000797	-	-
13 mm	-	-	-	2000798	-
16 mm	-	-	-	-	2000799

■ Normes	EN 818 ASTM 973
■ Classe	100
■ Matériel principal	Acier
■ Couleur	Bleu
■ Plage de température	-40°C / 200°C
■ Plage de température	-40°F / 120°F
■ Contenu des unités d'emballage (UE)	1

