



Clevis Shortening Claws with Safety Pin

Used to adjust the strand lengths of chain slings, lifting and lashing chains.

Item Name short	WLL kg [kg]	Chain Diameter	WLL t [t]	A [mm]	B [mm]	E [mm]	L [mm]
TWN 0851/1-6mm	1120	6 mm	1.12	27	37	51	78
TWN 0851/1-8mm	2000	8 mm	2	34	46	65	100
TWN 0851/1-10mm	3150	10 mm	3.15	43	56	81	124
TWN 0851/1-13mm	5300	13 mm	5.30	56	73	106	162
TWN 0851/1-16mm	8000	16 mm	8	68	88	130	193
TWN 0851/1-20mm	12500	20 mm	12.50	85	109	161	241
TWN 0851/1-22mm	15000	22 mm	15	94	120	177	271
TWN 0851/1-26mm	21200	26 mm	21.20	109	135	196	307
TWN 0851/1-32mm	31500	32 mm	31.50	135	166	240	376



Item Name short	Weight Net [kg]
TWN 0851/1-6mm	0.25
TWN 0851/1-8mm	0.50
TWN 0851/1-10mm	0.93
TWN 0851/1-13mm	2.03
TWN 0851/1-16mm	3.60
TWN 0851/1-20mm	6
TWN 0851/1-22mm	8
TWN 0851/1-26mm	13.20
TWN 0851/1-32mm	24.42



ORDER NUMBERS[Global Item Number/Local ERP Number SSNL]

Chain Diameter	TWN 0851/1-6mm	TWN 0851/1-8mm	TWN 0851/1-10mm	TWN 0851/1-13mm	TWN 0851/1-16mm	TWN 0851/1-20mm	TWN 0851/1-22mm	TWN 0851/1-26mm	TWN 0851/1-32mm
6 mm	2032527	-	-	-	-	-	-	-	-
8 mm	-	2032529	-	-	-	-	-	-	-
10 mm	-	-	2032530	-	-	-	-	-	-
13 mm	-	-	-	2032531	-	-	-	-	-
16 mm	-	-	-	-	2032532	-	-	-	-
20 mm	-	-	-	-	-	2032534	-	-	-
22 mm	-	-	-	-	-	-	2032535	-	-
26 mm	-	-	-	-	-	-	-	2032536	-
32 mm	-	-	-	-	-	-	-	-	2032537

■ Grade	80
■ Main Material	Steel
■ Colour	Red
■ Packaging Unit (PU) Content	1

