

Climbers Technical Double Slings Lanyard

Dynamic climbing lanyard can be clipped direct to anchors with a working length of 1m, or 2m and with the sling clipped around a structure at a working length of 1.5m.

Item Name short	Lanyard Leg Type	Energy Absorbing	Maximum User Weight [kg]	Length [m]	Anchor Connector	Harness Connector	Main Material
SP150 T CLIMA 2m 3LK2	Twin Loop Back	Yes	150	2	3LK2	1DK2	High-performance polyester

Item Name short	Inspection Guide	Multilingual User Instruction Manual	Packaging Unit (PU) Content	Individually Serial Numbered	Individual Certificate	Lifespan [yr.]	Colour
SP150 T CLIMA 2m 3LK2	Yes	Yes	1	Yes	Yes	10	Blue

ORDER NUMBERS[Global Item Number/Local ERP Number SSDE]

Length



3LK2

2 m

2031324
D095038X

■ Norms	EN 355: 2002
■ Anchor Connector	3LK2
■ Harness Connector	1DK2
■ Main Material	High-performance polyester
■ Colour	Blue
■ Energy Absorbing	Yes
■ Packaging Unit (PU) Content	1

SpanSet GmbH & Co. KG
Jülicher Straße 49-51
52531 Übach-Palenberg
Deutschland
+49 (0) 2451 4831-0
info@spanset.de
www.spanset.com



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written authorisation of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. DB040719 © SpanSet GmbH & Co. KG - Germany

**SpanSet
Certified
Safety**