



Corrente de agarrar Exoset® de 4 fios - GR100

Com anel oval e duas opções de gancho, autoblocante (CSLH) ou com fecho de segurança (CSHC).

Nome curto do item	CMU [kg]	Diâmetro da corrente	CMU [t]	Anel principal	L min. [m]	Cadeia	Ganchos
4-Exoset CSHC 6	-	6 mm	-	MLA-6-10	0.303	KLX-6-10	CSHC-6-10
4-Exoset CSLH 6	-	6 mm	-	MLA-6-10	0.328	KLX-6-10	CSLH-6-10
4-Exoset CSHC 8	-	8 mm	-	MLA-8-10	0.384	KLX-8-10	CSHC-8-10
4-Exoset CSLH 8	-	8 mm	-	MLA-8-10	0.412	KLX-8-10	CSLH-8-10
4-Exoset CSHC 10	-	10 mm	-	MLA-10-10	0.445	KLX-10-10	CSHC-10-10
4-Exoset CSLH 10	-	10 mm	-	MLA-10-10	0.478	KLX-10-10	CSLH-10-10
4-Exoset CSHC 16	-	16 mm	-	MLA-16-10	0.644	KLX-16-10	CSHC-16-10
4-Exoset CSLH 16	-	16 mm	-	MLA-16-10	0.704	KLX-16-10	CSLH-16-10
4-Exoset CRFX 6	2900	6 mm	2.9	Exoset MLA 3.5t	0.328	KLX-6-10	Exoset Clevis Safety Hook 1.4t 6mm
4-Exoset CRFX 8	5200	8 mm	5.2	Exoset MLA 6.5t	0.412	KLX-8-10	Exoset Clevis Safety Hook 2.5t 8mm
4-Exoset CRFX 10	8400	10 mm	8.4	Exoset MLA 11t	0.478	KLX-10-10	Exoset Clevis Safety Hook 4t 10mm
4-Exoset CRFX 13	13600	13 mm	13.6	Exoset MLA 17.5t	0.637	KLX-13-10	Exoset Clevis Safety Hook 6.7t 13mm
4-Exoset CSHC 13	14000	13 mm	14	MLA-13-10	0.593	KLX-13-10	CSHC-13-10
4-Exoset CSLH 13	14000	13 mm	14	MLA-13-10	0.637	KLX-13-10	CSLH-13-10
4-Exoset CRFX 16	21000	16 mm	21	Exoset MLA 21.2t	0.704	KLX-16-10	Exoset Clevis Safety Hook 10t 16mm



Nome curto do item	CMU 0° - 45° [t]	CMU [t] 45° - 60° CMU [t] 45° - 60° [t]	CMU 0° - 45° [kg]	CMU [Kg] 45° - 60° [kg]	Peso primeiro metro [kg]	Peso por metro [kg/m]
4-Exoset CSHC 6	2.9	2.1	2900	2100	7	3.6
4-Exoset CSLH 6	2.9	2.1	2900	2100	7	3.6
4-Exoset CSHC 8	5.2	3.7	5200	3700	8.4	6.4
4-Exoset CSLH 8	5.2	3.7	5200	3700	8.4	6.4
4-Exoset CSHC 10	8.4	6	8400	6000	17.2	10
4-Exoset CSLH 10	8.4	6	8400	6000	17.2	10
4-Exoset CSHC 16	21	15	21000	15000	51	26
4-Exoset CSLH 16	21	15	21000	15000	51	26
4-Exoset CRFX 6	2.9	2.1	2900	2100	-	-
4-Exoset CRFX 8	5.2	3.7	5200	3700	-	-
4-Exoset CRFX 10	8.4	6	8400	6000	-	-
4-Exoset CRFX 13	13.6	9.7	13600	9700	-	-
4-Exoset CSHC 13	14	10	14000	10000	31.5	17.2
4-Exoset CSLH 13	14	10	14000	10000	31.5	17.2
4-Exoset CRFX 16	21	15	21000	15000	-	-



NÚMEROS DE ORDEM[Global Item Number/Local ERP Number SSES]

CMU 0° - 45°	Ganchos	6 mm	8 mm	10 mm	13 mm	16 mm
2.9 t	 Exoset Clevis Safety Hook 1.4t 6mm	2009112	-	-	-	-
2.9 t	 CSLH-6-10	2026170 C1412026170DESC	-	-	-	-
2.9 t	 CSHC-6-10	2026165 C1412026165DESC	-	-	-	-
5.2 t	 Exoset Clevis Safety Hook 2.5t 8mm	-	2009114	-	-	-
5.2 t	 CSLH-8-10	-	2026171 C1412026171DESC	-	-	-
5.2 t	 CSHC-8-10	-	2026166 C1412026166DESC	-	-	-
8.4 t	 Exoset Clevis Safety Hook 4t 10mm	-	-	2009116	-	-
8.4 t	 CSLH-10-10	-	-	2026172 C1412026172DESC	-	-
8.4 t	 CSHC-10-10	-	-	2026167 C1412026167DESC	-	-
13.6 t	 Exoset Clevis Safety Hook 6.7t 13mm	-	-	-	2009118	-
14 t	 CSLH-13-10	-	-	-	2026173 C1412026173DESC	-
14 t	 CSHC-13-10	-	-	-	2026168 C1412026168DESC	-



CMU 0° - 45°	Ganchos	6 mm	8 mm	10 mm	13 mm	16 mm
21 t	 Exoset Clevis Safety Hook 10t 16mm	-	-	-	-	2009120
21 t	 CSLH-16-10	-	-	-	-	2026174 C1412026174DESC
21 t	 CSHC-16-10	-	-	-	-	2026169 C1412026169DESC

- Normas EN 818-4
- Grau 100
- Material principal Aço
- Cor Azul
- Gama de temperaturas -40° C to + 200° C
- Unidade de embalagem (PU) Contém 1

