


Corrente Exoset de Grau 10

Capacidade de carga 25% superior à do grau 8

Nome curto do item	CMU [kg]	Diâmetro da corrente	CMU [t]	D [mm]	E [mm]	H [mm]	Peso líquido [kg]
KLX-6-10	1400	6 mm	1.4	6	18	7.8	0.9
KLX-8-10	2500	8 mm	2.5	8	24	10.9	1.6
KLX-10-10	4000	10 mm	4	10	30	13	2.5
KLX-13-10	6700	13 mm	6.7	13	39	17.5	4.3
KLX-16-10	10000	16 mm	10	16	48	20.8	6.5



NÚMEROS DE ORDEM[Global Item Number/Local ERP Number SSES]

Diâmetro da corrente	KLX-6-10	KLX-8-10	KLX-10-10	KLX-13-10	KLX-16-10
6 mm	2000795 C10KLX000600020	-	-	-	-
8 mm	-	2000796 C10KLX000800020	-	-	-
10 mm	-	-	2000797 C10KLX001000020	-	-
13 mm	-	-	-	2000798 C10KLX001300020	-
16 mm	-	-	-	-	2000799 C10KLX001600020

■ Normas	EN 818 ASTM 973
■ Grau	100
■ Material principal	Aço
■ Cor	Azul
■ Gama de temperaturas	-40°C / 200°C
■ Gama de temperaturas	-40°F / 120°F
■ Unidade de embalagem (PU) Contém	1

