

D-Series 1Ply

Flat wide load bearing surface to minimise damage to fragile loads

Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Minimum Load Edge Radius [mm]
D-Series 1Ply 250kg 1.5m	250	025	1.5	0.3	25	2	6
D-Series 1Ply 250kg 2.0m	250	025	2.0	0.3	25	2	6
D-Series 1Ply 250kg 2.5m	250	025	2.5	0.3	25	2	6
D-Series 1Ply 250kg 3.0m	250	025	3.0	0.3	25	2	6
D-Series 1Ply 250kg 6.0m	250	025	6.0	0.3	25	2	6
D-Series 1Ply 250kg 8.0m	250	025	8.0	0.3	25	2	6
D-Series 1Ply 500kg 1.5m	500	0.5	1.5	0.3	35	2	6
D-Series 1Ply 500kg 2.0m	500	0.5	2.0	0.3	35	2	6
D-Series 1Ply 500kg 2.5m	500	0.5	2.5	0.3	35	2	6
D-Series 1Ply 500kg 3.0m	500	0.5	3.0	0.3	35	2	6
D-Series 1Ply 500kg 4.0m	500	0.5	4.0	0.3	35	2	6
D-Series 1Ply 500kg 6.0m	500	0.5	6.0	0.3	35	2	6
D-Series 1Ply 1000kg 1.5m	1000	1	1.5	0.3	50	3	9
D-Series 1Ply 1000kg 2.0m	1000	1	2.0	0.3	50	3	9
D-Series 1Ply 1000kg 2.5m	1000	1	2.5	0.3	50	3	9
D-Series 1Ply 1000kg 3.0m	1000	1	3.0	0.3	50	3	9
D-Series 1Ply 1000kg 4.0m	1000	1	4.0	0.3	50	3	9
D-Series 1Ply 1000kg 5.0m	1000	1	5.0	0.3	50	3	9
D-Series 1Ply 1000kg 6.0m	1000	1	6.0	0.3	50	3	9



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Minimum Load Edge Radius [mm]
D-Series 1Ply 1000kg 8.0m	1000	1	8.0	0.3	50	3	9
D-Series 1Ply 2000kg 1.5m	2000	2	1.5	0.4	75	4	12
D-Series 1Ply 2000kg 2.0m	2000	2	2.0	0.4	75	4	12
D-Series 1Ply 2000kg 2.5m	2000	2	2.5	0.4	75	4	12
D-Series 1Ply 2000kg 3.0m	2000	2	3.0	0.4	75	4	12
D-Series 1Ply 2000kg 4.0m	2000	2	4.0	0.4	75	4	12
D-Series 1Ply 2000kg 5.0m	2000	2	5.0	0.4	75	4	12
D-Series 1Ply 2000kg 6.0m	2000	2	6.0	0.4	75	4	12
D-Series 1Ply 2000kg 7.0m	2000	2	7.0	0.4	75	4	12
D-Series 1Ply 3000kg 1.5m	3000	3	1.5	0.6	100	4	12
D-Series 1Ply 3000kg 2.0m	3000	3	2.0	0.6	100	4	12
D-Series 1Ply 3000kg 2.5m	3000	3	2.5	0.6	100	4	12
D-Series 1Ply 3000kg 3.0m	3000	3	3.0	0.6	100	4	12
D-Series 1Ply 3000kg 4.0m	3000	3	4.0	0.6	100	4	12
D-Series 1Ply 3000kg 5.0m	3000	3	5.0	0.6	100	4	12
D-Series 1Ply 3000kg 6.0m	3000	3	6.0	0.6	100	4	12
D-Series 1Ply 3000kg 7.0m	3000	3	7.0	0.6	100	4	12
D-Series 1Ply 4000kg 1.5m	4000	4	1.5	0.6	140	4	12
D-Series 1Ply 4000kg 2.0m	4000	4	2.0	0.6	140	4	12
D-Series 1Ply 4000kg 2.5m	4000	4	2.5	0.6	140	4	12



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Minimum Load Edge Radius [mm]
D-Series 1Ply 4000kg 3.0m	4000	4	3.0	0.6	140	4	12
D-Series 1Ply 4000kg 4.0m	4000	4	4.0	0.6	140	4	12
D-Series 1Ply 4000kg 5.0m	4000	4	5.0	0.6	140	4	12
D-Series 1Ply 4000kg 6.0m	4000	4	6.0	0.6	140	4	12
D-Series 1Ply 5000kg 1.5m	5000	5	1.5	0.6	150	4	12
D-Series 1Ply 5000kg 2.0m	5000	5	2.0	0.6	150	4	12
D-Series 1Ply 5000kg 2.5m	5000	5	2.5	0.6	150	4	12
D-Series 1Ply 5000kg 3.0m	5000	5	3.0	0.6	150	4	12
D-Series 1Ply 5000kg 4.0m	5000	5	4.0	0.6	150	4	12
D-Series 1Ply 5000kg 6.0m	5000	5	6.0	0.6	150	4	12
D-Series 1Ply 6000kg 2.0m	6000	6	2.0	0.6	180	4	12
D-Series 1Ply 6000kg 4.0m	6000	6	4.0	0.6	180	4	12
D-Series 1Ply 6000kg 5.0m	6000	6	5.0	0.6	180	4	12
D-Series 1Ply 8000kg 3.0m	8000	8	3.0	0.6	240	5	15
D-Series 1Ply 8000kg 5.0m	8000	8	5.0	0.6	240	5	15
D-Series 1Ply 10000kg 5.0m	10000	10	5.0	0.7	300	5	15
D-Series 1Ply 10000kg 6.0m	10000	10	6.0	0.7	300	5	15

Item Name short	Colour
D-Series 1Ply 250kg 1.5m	Olive
D-Series 1Ply 250kg 2.0m	Olive



Item Name short	Colour
D-Series 1Ply 250kg 2.5m	Olive
D-Series 1Ply 250kg 3.0m	Olive
D-Series 1Ply 250kg 6.0m	Olive
D-Series 1Ply 250kg 8.0m	Olive
D-Series 1Ply 500kg 1.5m	Olive
D-Series 1Ply 500kg 2.0m	Olive
D-Series 1Ply 500kg 2.5m	Olive
D-Series 1Ply 500kg 3.0m	Olive
D-Series 1Ply 500kg 4.0m	Olive
D-Series 1Ply 500kg 6.0m	Olive
D-Series 1Ply 1000kg 1.5m	Purple
D-Series 1Ply 1000kg 2.0m	Purple
D-Series 1Ply 1000kg 2.5m	Purple
D-Series 1Ply 1000kg 3.0m	Purple
D-Series 1Ply 1000kg 4.0m	Purple
D-Series 1Ply 1000kg 5.0m	Purple
D-Series 1Ply 1000kg 6.0m	Purple
D-Series 1Ply 1000kg 8.0m	Purple
D-Series 1Ply 2000kg 1.5m	Green
D-Series 1Ply 2000kg 2.0m	Green
D-Series 1Ply 2000kg 2.5m	Green
D-Series 1Ply 2000kg 3.0m	Green
D-Series 1Ply 2000kg 4.0m	Green
D-Series 1Ply 2000kg 5.0m	Green
D-Series 1Ply 2000kg 6.0m	Green
D-Series 1Ply 2000kg 7.0m	Green
D-Series 1Ply 3000kg 1.5m	Yellow



Item Name short	Colour
D-Series 1Ply 3000kg 2.0m	Yellow
D-Series 1Ply 3000kg 2.5m	Yellow
D-Series 1Ply 3000kg 3.0m	Yellow
D-Series 1Ply 3000kg 4.0m	Yellow
D-Series 1Ply 3000kg 5.0m	Yellow
D-Series 1Ply 3000kg 6.0m	Yellow
D-Series 1Ply 3000kg 7.0m	Yellow
D-Series 1Ply 4000kg 1.5m	Grey
D-Series 1Ply 4000kg 2.0m	Grey
D-Series 1Ply 4000kg 2.5m	Grey
D-Series 1Ply 4000kg 3.0m	Grey
D-Series 1Ply 4000kg 4.0m	Grey
D-Series 1Ply 4000kg 5.0m	Grey
D-Series 1Ply 4000kg 6.0m	Grey
D-Series 1Ply 5000kg 1.5m	Red
D-Series 1Ply 5000kg 2.0m	Red
D-Series 1Ply 5000kg 2.5m	Red
D-Series 1Ply 5000kg 3.0m	Red
D-Series 1Ply 5000kg 4.0m	Red
D-Series 1Ply 5000kg 6.0m	Red
D-Series 1Ply 6000kg 2.0m	Brown
D-Series 1Ply 6000kg 4.0m	Brown
D-Series 1Ply 6000kg 5.0m	Brown
D-Series 1Ply 8000kg 3.0m	Blue
D-Series 1Ply 8000kg 5.0m	Blue
D-Series 1Ply 10000kg 5.0m	Orange
D-Series 1Ply 10000kg 6.0m	Orange



ORDER NUMBERS[Global Item Number/Local ERP Number SSAU]

Dimension L1	250 kg	500 kg	1000 kg	2000 kg	3000 kg	4000 kg	5000 kg	6000 kg	8000 kg	10000 kg
1.5 m	2029223 D0250-0x1.5	2029229 D0500-0x1.5	2029239 D1000-0x1.5	2029247 D2000-0x1.5	2029255 D3000-0x1.5	2029263 D4000-0x1.5	2029270 D5000-0x1.5	-	-	-
2.0 m	2029224 D0250-0x2.0	2029230 D0500-0x2.0	2029240 D1000-0x2.0	2029248 D2000-0x2.0	2029256 D3000-0x2.0	2029264 D4000-0x2.0	2029271 D5000-0x2.0	2029276 D6000-0x2.0	-	-
2.5 m	2029225 D0250-0x2.5	2029231 D0500-0x2.5	2029241 D1000-0x2.5	2029249 D2000-0x2.5	2029257 D3000-0x2.5	2029265 D4000-0x2.5	2029272 D5000-0x2.5	-	-	-
3.0 m	2029226 D0250-0x3.0	2029236 D0500-0x3.0	2029242 D1000-0x3.0	2029250 D2000-0x3.0	2029258 D3000-0x3.0	2029266 D4000-0x3.0	2029273 D5000-0x3.0	-	2029279 D8000-0x3.0	-
4.0 m	-	2029237 D0500-0x4.0	2029243 D1000-0x4.0	2029251 D2000-0x4.0	2029259 D3000-0x4.0	2029267 D4000-0x4.0	2029274 D5000-0x4.0	2029277 D6000-0x4.0	-	-
5.0 m	-	-	2029244 D1000-0x5.0	2029252 D2000-0x5.0	2029260 D3000-0x5.0	2029268 D4000-0x5.0	-	2029278 D6000-0x5.0	2029280 D8000-0x5.0	2029281 D10000-0x5.0
6.0 m	2029227 D0250-0x6.0	2029238 D0500-0x6.0	2029245 D1000-0x6.0	2029253 D2000-0x6.0	2029261 D3000-0x6.0	2029269 D4000-0x6.0	2029275 D5000-0x6.0	-	-	2029282 D10000-0x6.0
7.0 m	-	-	-	2029254 D2000-0x7.0	2029262 D3000-0x7.0	-	-	-	-	-
8.0 m	2029228 D0250-0x8.0	-	2029246 D1000-0x8.0	-	-	-	-	-	-	-

■ Standards	AS 1353.1
■ Main Material	Polyester
■ Temperature Range	-40°C to 100°C
■ Number of layers	1
■ Packaging Unit (PU) Content	1

SpanSet Australia Ltd
150 Old Bathurst Road
Emu Plains NSW 2750
Australia
+61 (02) 4735 3955
sales@spanset.com.au
www.spanset.com.au



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Australia Ltd

**SpanSet
Certified
Safety**