

DSL3 Fall Arrest Lanyard

Combine an auto shortening lanyard with a fully certified energy absorber



Item Name short	Energy Absorbing	Maximum User Weight [kg]	Quality	Anchor Connector	Harness Connector	L [m]	Relieved Length [m]
SP140-DSL3 S HL 2m 3CK2	Yes	150	Professional	3CK2	3DK3	2	0.7

Item Name short	Weight Net [kg]	Main Material	Inspection Guide	Packaging Unit (PU) Content	Individually Serial Numbered	Individual Certificate	Lifespan [yr.]
SP140-DSL3 S HL 2m 3CK2	1.15	High molecular weight polyethylene (HMPE)	Yes	1	Yes	Yes	10

Item Name short	Colour
SP140-DSL3 S HL 2m 3CK2	Neon yellow

ORDER NUMBERS[Global Item Number/Local ERP Number SSUK]

Anchor Connector

SP140-DSL3 S HL 2m 3CK2



3CK2

2026228
111316

■ Norms	EN 355: 2002
■ Anchor Connector	3CK2
■ Harness Connector	3DK3
■ Main Material	High molecular weight polyethylene (HMPE)
■ Colour	Neon yellow
■ Relieved Length	0.7 m
■ Weight Net	1.15 kg
■ Fall Equipment Type	Fall Arrest
■ Energy Absorbing	Yes
■ Label Protection	Yes
■ Packaging Unit (PU) Content	1

