


DSL3 Fall Arrest Lanyard Single

Combine an auto shortening lanyard with a fully certified energy absorber

Item Name short	Anchor Connector	Relieved Length [m]
DSL3 S HL 2m 1DK2	1DK2	0.7
DSL3 S HL 2m 3CK2	3CK2	0.7
DSL3 S HL 2m 1RH2	1RH2 Lite	0.8
DSL3 S HL 2m 3RH2A	3RH2A	0.8



ORDER NUMBERS[Global Item Number/Local ERP Number SSNL]

Anchor Connector	DSL3 S HL 2m 1DK2	DSL3 S HL 2m 1RH2	DSL3 S HL 2m 3CK2	DSL3 S HL 2m 3RH2A
 1DK2	2025516	-	-	-
 1RH2 Lite	-	2025517	-	-
 3CK2	-	-	2025518	-
 3RH2A	-	-	-	2025519

■ Norms	EN 355: 2002
■ Harness Connector	3DK3
■ Main Material	High molecular weight polyethylene (HMPE)
■ Colour	Neon yellow
■ Energy Absorbing	Yes
■ Label Protection	Yes

SpanSet Nederland B.V.
 Plaza 10A 4782 SK
 Moerdijk Nederland
 Tel.: +31 (0) 168 38 68 00
 info@spanset.nl
 www.spanset.nl



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed via electronic systems without the written permission of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Nederland B.V.

**SpanSet
 Certified
 Safety**

