


### DSL3 Fall Arrest Lanyard Single

Combine an auto shortening lanyard with a fully certified energy absorber



Item Name short	Anchor Connector	Relieved Length [m]
DSL3 S HL 2m 1DK2	1DK2	0.7
DSL3 S HL 2m 3CK2	3CK2	0.7
DSL3 S HL 2m 1RH2	1RH2 Lite	0.8
DSL3 S HL 2m 3RH2A	3RH2A	0.8



#### ORDER NUMBERS[Global Item Number/Local ERP Number SSUK]

Anchor Connector	DSL3 S HL 2m 1DK2	DSL3 S HL 2m 1RH2	DSL3 S HL 2m 3CK2	DSL3 S HL 2m 3RH2A
1DK2	2025516	-	-	-
1RH2 Lite	-	2025517	-	-
3CK2	-	-	2025518	-
3RH2A	-	-	-	2025519

■ Norms	EN 355: 2002
■ Harness Connector	3DK3
■ Main Material	High molecular weight polyethylene (HMPE)
■ Colour	Neon yellow
■ Fall Equipment Type	Fall Arrest
■ Energy Absorbing	Yes

**SpanSet (UK) Limited**  
 Telford Way  
 Middlewich Cheshire  
 CW10 0HX United Kingdom  
 +44 (0) 1606 737494  
 info@spanset.co.uk  
 www.spanset.co.uk



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

**SpanSet  
 Certified  
 Safety**

- Label Protection Yes
- Packaging Unit (PU) Content 1

