

DSL3 Fall Arrest Lanyard Twin

Combine an auto shortening lanyard with a fully certified energy absorber

Item Name short	Energy Absorbing	Maximum User Weight [kg]	Quality	Anchor Connector	Harness Connector	L [m]	Relieved Length [m]
DSL3 T HL 2m 1RH2	Yes	150	Professional	1RH2	3DK3	2	0.8

Item Name short	Main Material	Inspection Guide	Packaging Unit (PU) Content	Individually Serial Numbered	Individual Certificate	Lifespan [yr.]	Colour
DSL3 T HL 2m 1RH2	High molecular weight polyethylene (HMPE)	Yes	1	Yes	Yes	10	Neon yellow

ORDER NUMBERS[Global Item Number/Local ERP Number SSDE]

Anchor Connector

DSL3 T HL 2m 1RH2



1RH2

2025521
D091150X

■ Norms	EN 355: 2002
■ Anchor Connector	1RH2
■ Harness Connector	3DK3
■ Main Material	High molecular weight polyethylene (HMPE)
■ Colour	Neon yellow
■ Relieved Length	0.8 m
■ Energy Absorbing	Yes
■ Label Protection	Yes
■ Packaging Unit (PU) Content	1

SpanSet GmbH & Co. KG
Jülicher Straße 49-51
52531 Übach-Palenberg
Deutschland
+49 (0) 2451 4831-0
info@spanset.de
www.spanset.com



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written authorisation of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. DB040719 © SpanSet GmbH & Co. KG - Germany

**SpanSet
Certified
Safety**