




### DSL3 Fall Arrest Lanyard Twin

Combine an auto shortening lanyard with a fully certified energy absorber

Item Name short	Energy Absorbing	Maximum User Weight [kg]	Quality	Anchor Connector	Harness Connector	L [m]	Relieved Length [m]
DSL3 T HL 2m 1RH2	Yes	150	Professional	1RH2	3DK3	2	0.8

Item Name short	Main Material	Inspection Guide	Packaging Unit (PU) Content	Individually Serial Numbered	Individual Certificate	Lifespan [yr.]	Colour
DSL3 T HL 2m 1RH2	High molecular weight polyethylene (HMPE)	Yes	1	Yes	Yes	10	Neon yellow



### ORDER NUMBERS[Global Item Number/Local ERP Number SSID]

Anchor Connector

DSL3 T HL 2m 1RH2



1RH2

2025521

- Norms EN 355: 2002
- Anchor Connector 1RH2
- Harness Connector 3DK3
- Main Material High molecular weight polyethylene (HMPE)
- Colour Neon yellow
- Relieved Length 0.8 m
- Energy Absorbing Yes
- Label Protection Yes
- Packaging Unit (PU) Content 1

**SpanSet Indonesia**  
 Marunda Center Blok F No.20 Segara Makmur, Tarumajaya. Bekasi. Indonesia. 17211  
 +62 21 285 100 77  
 sales@spanset.co.id  
 www.spanset.co.id



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Indonesia - Indonesia

**SpanSet  
 Certified  
 Safety**