




DSL3 Fall Arrest Lanyard Twin

Combine an auto shortening lanyard with a fully certified energy absorber

| Item Name short | Anchor Connector | Relieved Length [m] |
|--------------------|------------------|---------------------|
| DSL3 T HL 2m 1DK2 | 1DK2 | 0.7 |
| DSL3 T HL 2m 3CK2 | 3CK2 | 0.7 |
| DSL3 T HL 2m 1RH2 | 1RH2 | 0.8 |
| DSL3 T HL 2m 3RH2A | 3RH2A | 0.8 |



ORDER NUMBERS[Global Item Number/Local ERP Number SSUK]

| Anchor Connector | DSL3 T HL 2m 1DK2 | DSL3 T HL 2m 1RH2 | DSL3 T HL 2m 3CK2 | DSL3 T HL 2m 3RH2A |
|------------------|-------------------|-------------------|-------------------|--------------------|
| 1DK2 | 2025520 | - | - | - |
| 1RH2 | - | 2025521 | - | - |
| 3CK2 | - | - | 2025522 | - |
| 3RH2A | - | - | - | 2025523 |

- Norms EN 355: 2002
- Harness Connector 3DK3
- Main Material High molecular weight polyethylene (HMPE)
- Colour Neon yellow
- Fall Equipment Type Fall Arrest
- Energy Absorbing Yes
- Label Protection Yes
- Packaging Unit (PU) Content 1

SpanSet (UK) Limited
Telford Way
Middlewich Cheshire
CW10 0HX United Kingdom
+44 (0) 1606 737494
info@spanset.co.uk
www.spanset.co.uk



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

**SpanSet
Certified
Safety**