




DSL3 Fall Arrest Lanyard Twin

Combine an auto shortening lanyard with a fully certified energy absorber

Item Name short	Energy Absorbing	Maximum User Weight [kg]	Quality	Anchor Connector	Harness Connector	L [m]	Relieved Length [m]
DSL3 T HL 2m 1RH2	Yes	150	Profesional	1RH2	3DK3	2	0.8

Item Name short	Main Material	Inspection Guide	Packaging Unit (PU) Content	Individually Serial Numbered	Individual Certificate	Lifespan [yr.]	Colour
DSL3 T HL 2m 1RH2	High molecular weight polyethylene (HMPE)	Yes	1	Yes	Yes	10	Neon yellow



NOMOR PESANAN[Global Item Number/Local ERP Number SSID]

Anchor Connector

DSL3 T HL 2m 1RH2



1RH2

2025521

- Norms EN 355: 2002
- Anchor Connector 1RH2
- Harness Connector 3DK3
- Main Material High molecular weight polyethylene (HMPE)
- Colour Neon yellow
- Relieved Length 0.8 m
- Energy Absorbing Yes
- Label Protection Yes
- Packaging Unit (PU) Content 1

SpanSet Indonesia
Marunda Center Blok F No.20 Segara Makmur, Tarumajaya. Bekasi, Indonesia. 17211
+62 21 285 100 77
sales@spanset.co.id
www.spanset.co.id



Tunduk pada perubahan teknis. Seluruh hak cipta dilindungi. Tidak ada satu bagianpun dari Lembar Data Teknis ini yang boleh diproduksi ulang dalam bentuk apapun (print, fotokopi, mikrofilm atau proses lain manapun) atau diproses, diduplikat maupun dibagikan melalui sistem elektronik tanpa persetujuan tertulis dari SpanSet. Lembar Data Teknis ini telah dipersiapkan dengan hati-hati; SpanSet tidak bertanggung jawab atas kesalahan maupun kelalaian yang terjadi. © SpanSet Indonesia - Indonesia

**SpanSet
Certified
Safety**