

Dynamic Self-Retracting Lanyard

Innovative Hybrid Lanyard Technology reducing clearance heights for workers

Item Name short	Energy Absorbing	Maximum User Weight [kg]	Quality	Anchor Connector	Harness Connector	L [m]	Weight Net [kg]
DSL2 T HL 2m 1RH2	Yes	140	Professional	1RH2	3DK3	2	1.6

Item Name short	Main Material	Inspection Guide	Packaging Unit (PU) Content	Individually Serial Numbered	Individual Certificate	Lifespan [yr.]	Colour
DSL2 T HL 2m 1RH2	High-performance polyester	Yes	1	Yes	Yes	10	Black

ORDER NUMBERS[Global Item Number/Local ERP Number SSID]

Anchor Connector

DSL2 T HL 2m 1RH2



1RH2

2004132

■ Norms	EN 360: 2002
■ Anchor Connector	1RH2
■ Harness Connector	3DK3
■ Main Material	High-performance polyester
■ Colour	Black
■ Weight Net	1.6 kg
■ Energy Absorbing	Yes
■ Label Protection	Yes
■ Packaging Unit (PU) Content	1

SpanSet Indonesia
 Marunda Center Blok
 F No.20 Segara
 Makmur, Tarumajaya.
 Bekasi, Indonesia.
 17211
 +62 21 285 100 77
 sales@spanset.co.id
 www.spanset.co.id



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Indonesia - Indonesia

**SpanSet
 Certified
 Safety**