

E-Series

Original SpanSet, Now a Generic Term for Round Slings

Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Minimum Load Edge Radius [mm]
E1000-0x0.5	1000	1	0.5	0.5	45	6	18
E1000-0x1.0	1000	1	1	0.5	45	6	18
E1000-0x1.5	1000	1	1.5	0.5	45	6	18
E1000-0x2.0	1000	1	2	0.5	45	6	18
E1000-0x2.5	1000	1	2.5	0.5	45	6	18
E1000-0x3.0	1000	1	3	0.5	45	6	18
E1000-0x4.0	1000	1	4	0.5	45	6	18
E1000-0x5.0	1000	1	5	0.5	45	6	18
E1000-0x6.0	1000	1	6	0.5	45	6	18
E1000-0x7.0	1000	1	7	0.5	45	6	18
E1000-0x8.0	1000	1	8	0.5	45	6	18
E2000-0x0.5	2000	2	0.5	0.5	48	7	21
E2000-0x1.0	2000	2	1	0.5	48	7	21
E2000-0x1.5	2000	2	1.5	0.5	48	7	21
E2000-0x2.0	2000	2	2	0.5	48	7	21
E2000-0x2.5	2000	2	2.5	0.5	48	7	21
E2000-0x3.0	2000	2	3	0.5	48	7	21
E2000-0x4.0	2000	2	4	0.5	48	7	21
E2000-0x5.0	2000	2	5	0.5	48	7	21
E2000-0x6.0	2000	2	6	0.5	48	7	21
E2000-0x7.0	2000	2	7	0.5	48	7	21
E2000-0x8.0	2000	2	8	0.5	48	7	21
E3000-0x0.5	3000	3	0.5	0.5	60	8	24
E3000-0x1.0	3000	3	1	0.5	60	8	24
E3000-0x1.5	3000	3	1.5	0.5	60	8	24
E3000-0x2.0	3000	3	2	0.5	60	8	24
E3000-0x2.5	3000	3	2.5	0.5	60	8	24
E3000-0x3.0	3000	3	3	0.5	60	8	24
E3000-0x4.0	3000	3	4	0.5	60	8	24
E3000-0x5.0	3000	3	5	0.5	60	8	24
E3000-0x6.0	3000	3	6	0.5	60	8	24



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Minimum Load Edge Radius [mm]
E3000-0x7.0	3000	3	7	0.5	60	8	24
E3000-0x8.0	3000	3	8	0.5	60	8	24
E4000-0x1.0	4000	4	1	1.0	65	10	30
E4000-0x1.5	4000	4	1.5	1.0	65	10	30
E4000-0x2.0	4000	4	2	1.0	65	10	30
E4000-0x2.5	4000	4	2.5	1.0	65	10	30
E4000-0x3.0	4000	4	3	1.0	65	10	30
E4000-0x4.0	4000	4	4	1.0	65	10	30
E4000-0x5.0	4000	4	5	1.0	65	10	30
E4000-0x6.0	4000	4	6	1.0	65	10	30
E4000-0x7.0	4000	4	7	1.0	65	10	30
E4000-0x8.0	4000	4	8	1.0	65	10	30
E5000-0x1.0	5000	5	1	1.0	75	10	30
E5000-0x1.5	5000	5	1.5	1.0	75	10	30
E5000-0x2.0	5000	5	2	1.0	75	10	30
E5000-0x2.5	5000	5	2.5	1.0	75	10	30
E5000-0x3.0	5000	5	3	1.0	75	10	30
E5000-0x4.0	5000	5	4	1.0	75	10	30
E5000-0x5.0	5000	5	5	1.0	75	10	30
E5000-0x6.0	5000	5	6	1.0	75	10	30
E5000-0x7.0	5000	5	7	1.0	75	10	30
E5000-0x8.0	5000	5	8	1.0	75	10	30
E6000-0x1.0	6000	6	1	1.0	80	13	39
E6000-0x1.5	6000	6	1.5	1.0	80	13	39
E6000-0x2.0	6000	6	2	1.0	80	13	39
E6000-0x2.5	6000	6	2.5	1.0	80	13	39
E6000-0x3.0	6000	6	3	1.0	80	13	39
E6000-0x4.0	6000	6	4	1.0	80	13	39
E6000-0x5.0	6000	6	5	1.0	80	13	39
E6000-0x6.0	6000	6	6	1.0	80	13	39
E6000-0x7.0	6000	6	7	1.0	80	13	39
E6000-0x8.0	6000	6	8	1.0	80	13	39



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Contact Width Under Load [mm]	Contact Thickness Under Load [mm]	Minimum Load Edge Radius [mm]
E8000-0x1.0	8000	8	1	1.0	80	15	45
E8000-0x1.5	8000	8	1.5	1.0	80	15	45
E8000-0x2.0	8000	8	2	1.0	80	15	45
E8000-0x2.5	8000	8	2.5	1.0	80	15	45
E8000-0x3.0	8000	8	3	1.0	80	15	45
E8000-0x4.0	8000	8	4	1.0	80	15	45
E8000-0x5.0	8000	8	5	1.0	80	15	45
E8000-0x6.0	8000	8	6	1.0	80	15	45
E8000-0x7.0	8000	8	7	1.0	80	15	45
E8000-0x8.0	8000	8	8	1.0	80	15	45

Item Name short	Weight Net [kg]	Weight per Meter [kg/m]	Colour
E1000-0x0.5	0.15	0.3	Purple
E1000-0x1.0	0.3	0.3	Purple
E1000-0x1.5	0.45	0.3	Purple
E1000-0x2.0	0.6	0.3	Purple
E1000-0x2.5	0.75	0.3	Purple
E1000-0x3.0	0.9	0.3	Purple
E1000-0x4.0	1.2	0.3	Purple
E1000-0x5.0	1.5	0.3	Purple
E1000-0x6.0	1.8	0.3	Purple
E1000-0x7.0	2.1	0.3	Purple
E1000-0x8.0	2.4	0.3	Purple
E2000-0x0.5	0.25	0.5	Green
E2000-0x1.0	0.5	0.5	Green
E2000-0x1.5	0.75	0.5	Green
E2000-0x2.0	1	0.5	Green



Item Name short	Weight Net [kg]	Weight per Meter [kg/m]	Colour
E2000-0x2.5	1.25	0.5	Green
E2000-0x3.0	1.5	0.5	Green
E2000-0x4.0	2	0.5	Green
E2000-0x5.0	2.5	0.5	Green
E2000-0x6.0	3	0.5	Green
E2000-0x7.0	3	0.5	Green
E2000-0x8.0	4	0.5	Green
E3000-0x0.5	0.4	0.8	Yellow
E3000-0x1.0	0.8	0.8	Yellow
E3000-0x1.5	1.2	0.8	Yellow
E3000-0x2.0	1.6	0.8	Yellow
E3000-0x2.5	2	0.8	Yellow
E3000-0x3.0	2.4	0.8	Yellow
E3000-0x4.0	3.2	0.8	Yellow
E3000-0x5.0	4	0.8	Yellow
E3000-0x6.0	4.8	0.8	Yellow
E3000-0x7.0	5.6	0.8	Yellow
E3000-0x8.0	6.4	0.8	Yellow
E4000-0x1.0	1	1.0	Grey
E4000-0x1.5	1.5	1.0	Grey
E4000-0x2.0	2	1.0	Grey
E4000-0x2.5	2.5	1.0	Grey
E4000-0x3.0	3	1.0	Grey
E4000-0x4.0	4	1.0	Grey
E4000-0x5.0	5	1.0	Grey
E4000-0x6.0	6	1.0	Grey



Item Name short	Weight Net [kg]	Weight per Meter [kg/m]	Colour
E4000-0x7.0	7	1.0	Grey
E4000-0x8.0	8	1.0	Grey
E5000-0x1.0	1.2	1.2	Red
E5000-0x1.5	1.8	1.2	Red
E5000-0x2.0	2.4	1.2	Red
E5000-0x2.5	3	1.2	Red
E5000-0x3.0	3.6	1.2	Red
E5000-0x4.0	4.8	1.2	Red
E5000-0x5.0	6	1.2	Red
E5000-0x6.0	7.2	1.2	Red
E5000-0x7.0	8.4	1.2	Red
E5000-0x8.0	9.6	1.2	Red
E6000-0x1.0	1.4	1.4	Brown
E6000-0x1.5	2.1	1.4	Brown
E6000-0x2.0	2.8	1.4	Brown
E6000-0x2.5	3.5	1.4	Brown
E6000-0x3.0	4.2	1.4	Brown
E6000-0x4.0	5.6	1.4	Brown
E6000-0x5.0	7	1.4	Brown
E6000-0x6.0	8.4	1.4	Brown
E6000-0x7.0	9.8	1.4	Brown
E6000-0x8.0	11.2	1.4	Brown
E8000-0x1.0	1.8	1.8	Blue
E8000-0x1.5	2.7	1.8	Blue
E8000-0x2.0	3.6	1.8	Blue
E8000-0x2.5	4.5	1.8	Blue



Item Name short	Weight Net [kg]	Weight per Meter [kg/m]	Colour
E8000-0x3.0	5.4	1.8	Blue
E8000-0x4.0	7.2	1.8	Blue
E8000-0x5.0	9	1.8	Blue
E8000-0x6.0	10.8	1.8	Blue
E8000-0x7.0	12.6	1.8	Blue
E8000-0x8.0	14.4	1.8	Blue

ORDER NUMBERS[Global Item Number/Local ERP Number SSAU]

Dimension L1	1000 kg	2000 kg	3000 kg	4000 kg	5000 kg	6000 kg	8000 kg
0.5 m	2027932 E1000-0x0.5	2027937 E2000-0x0.5	2028263 E3000-0x0.5	-	-	-	-
1 m	2027933 E1000-0x1.0	2027938 E2000-0x1.0	2028725 E3000-0x1.0	2028735 E4000-0x1.0	2028745 E5000-0x1.0	2028755 E6000-0x1.0	2028765 E8000-0x1.0
1.5 m	2027934 E1000-0x1.5	2027939 E2000-0x1.5	2028726 E3000-0x1.5	2028736 E4000-0x1.5	2028746 E5000-0x1.5	2028756 E6000-0x1.5	2028766 E8000-0x1.5
2 m	2027935 E1000-0x2.0	2028718 E2000-0x2.0	2028727 E3000-0x2.0	2028737 E4000-0x2.0	2028747 E5000-0x2.0	2028757 E6000-0x2.0	2028767 E8000-0x2.0
2.5 m	2027936 E1000-0x2.5	2028719 E2000-0x2.5	2028728 E3000-0x2.5	2028738 E4000-0x2.5	2028748 E5000-0x2.5	2028758 E6000-0x2.5	2028768 E8000-0x2.5
3 m	2028260 E1000-0x3.0	2028720 E2000-0x3.0	2028729 E3000-0x3.0	2028739 E4000-0x3.0	2028749 E5000-0x3.0	2028759 E6000-0x3.0	2028769 E8000-0x3.0
4 m	2028713 E1000-0x4.0	2028721 E2000-0x4.0	2028730 E3000-0x4.0	2028740 E4000-0x4.0	2028750 E5000-0x4.0	2028760 E6000-0x4.0	2028770 E8000-0x4.0
5 m	2028714 E1000-0x5.0	2028722 E2000-0x5.0	2028731 E3000-0x5.0	2028741 E4000-0x5.0	2028751 E5000-0x5.0	2028761 E6000-0x5.0	2028771 E8000-0x5.0
6 m	2028715 E1000-0x6.0	2028723 E2000-0x6.0	2028732 E3000-0x6.0	2028742 E4000-0x6.0	2028752 E5000-0x6.0	2028762 E6000-0x6.0	2028772 E8000-0x6.0
7 m	2028716 E1000-0x7.0	2029030 E2000-0x7.0	2028733 E3000-0x7.0	2028743 E4000-0x7.0	2028753 E5000-0x7.0	2028763 E6000-0x7.0	2028773 E8000-0x7.0
8 m	2028717 E1000-0x8.0	2028724 E2000-0x8.0	2028734 E3000-0x8.0	2028744 E4000-0x8.0	2028754 E5000-0x8.0	2028764 E6000-0x8.0	2028774 E8000-0x8.0

- Standards AS 4497:2018
- Main Material Polyester
- Temperature Range -40°C to 100°C
- Label Protection No
- Packaging Unit (PU) Content 1

SpanSet Australia Ltd
150 Old Bathurst Road
Emu Plains NSW 2750
Australia
+61 (02) 4735 3955
sales@spanset.com.au
www.spanset.com.au



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Australia Ltd

**SpanSet
Certified
Safety**

