

### Eco heavy-duty

Standard heavy-duty polyester lifting round sling



| Item Name short | WLL kg [kg] | WLL t [t] | L1 [m] | Contact Width Under Load [mm] | Contact Thickness Under Load [mm] | Weight Net [kg] |
|-----------------|-------------|-----------|--------|-------------------------------|-----------------------------------|-----------------|
| RS 10000 1.5m   | 10000       | 10        | 1.5    | 99                            | 15                                | -               |
| RS 10000 2m     | 10000       | 10        | 2      | 99                            | 15                                | -               |
| RS 10000 3m     | 10000       | 10        | 3      | 99                            | 15                                | 7.8             |
| RS 10000 4m     | 10000       | 10        | 4      | 99                            | 15                                | 8.6             |
| RS 10000 5m     | 10000       | 10        | 5      | 99                            | 15                                | 9.4             |
| RS 10000 6m     | 10000       | 10        | 6      | 99                            | 15                                | 10.2            |
| RS 10000 10m    | 10000       | 10        | 10     | 99                            | 15                                | -               |
| RS 15000 2m     | 15000       | 15        | 2      | 115                           | 16                                | -               |
| RS 15000 3m     | 15000       | 15        | 3      | 115                           | 16                                | 8.4             |
| RS 15000 4m     | 15000       | 15        | 4      | 115                           | 16                                | 9.1             |
| RS 15000 5m     | 15000       | 15        | 5      | 115                           | 16                                | 10              |
| RS 15000 6m     | 15000       | 15        | 6      | 115                           | 16                                | 10.9            |
| RS 15000 8m     | 15000       | 15        | 8      | 115                           | 16                                | -               |
| RS 20000 1m     | 20000       | 20        | 1      | 140                           | 20                                | -               |
| RS 20000 1.5m   | 20000       | 20        | 1.5    | 140                           | 20                                | -               |
| RS 20000 2m     | 20000       | 20        | 2      | 140                           | 20                                | -               |
| RS 20000 3m     | 20000       | 20        | 3      | 140                           | 20                                | 9.2             |
| RS 20000 4m     | 20000       | 20        | 4      | 140                           | 20                                | 9.9             |
| RS 20000 5m     | 20000       | 20        | 5      | 140                           | 20                                | 10.8            |
| RS 20000 6m     | 20000       | 20        | 6      | 140                           | 20                                | 11.7            |
| RS 20000 8m     | 20000       | 20        | 8      | 140                           | 20                                | -               |
| RS 25000 2m     | 25000       | 25        | 2      | 153                           | 23                                | -               |
| RS 25000 3m     | 25000       | 25        | 3      | 153                           | 23                                | 9.6             |
| RS 25000 4m     | 25000       | 25        | 4      | 153                           | 23                                | 10.4            |
| RS 25000 5m     | 25000       | 25        | 5      | 153                           | 23                                | 11.2            |
| RS 25000 6m     | 25000       | 25        | 6      | 153                           | 23                                | 12              |
| RS 25000 8m     | 25000       | 25        | 8      | 153                           | 23                                | -               |
| RS 25000 10m    | 25000       | 25        | 10     | 153                           | 23                                | -               |
| RS 25000 12m    | 25000       | 25        | 12     | 153                           | 23                                | 24              |



| Item Name short | WLL kg [kg] | WLL t [t] | L1 [m] | Contact Width Under Load [mm] | Contact Thickness Under Load [mm] | Weight Net [kg] |
|-----------------|-------------|-----------|--------|-------------------------------|-----------------------------------|-----------------|
| RS 30000 2m     | 30000       | 30        | 2      | 167                           | 24                                | -               |
| RS 30000 3m     | 30000       | 30        | 3      | 167                           | 24                                | 10.2            |
| RS 30000 4m     | 30000       | 30        | 4      | 167                           | 24                                | 11              |
| RS 30000 6m     | 30000       | 30        | 6      | 167                           | 24                                | 12.6            |
| RS 30000 15m    | 30000       | 30        | 15     | 167                           | 24                                | -               |
| RS 40000 2m     | 40000       | 40        | 2      | -                             | -                                 | -               |
| RS 40000 3m     | 40000       | 40        | 3      | -                             | -                                 | -               |
| RS 40000 4m     | 40000       | 40        | 4      | -                             | -                                 | -               |
| RS 40000 5m     | 40000       | 40        | 5      | -                             | -                                 | -               |
| RS 40000 6m     | 40000       | 40        | 6      | -                             | -                                 | -               |
| RS 50000 3m     | 50000       | 50        | 3      | -                             | -                                 | -               |
| RS 50000 4m     | 50000       | 50        | 4      | -                             | -                                 | -               |
| RS 50000 5m     | 50000       | 50        | 5      | -                             | -                                 | -               |
| RS 60000 4m     | 60000       | 60        | 4      | -                             | -                                 | -               |
| RS 60000 5m     | 60000       | 60        | 5      | -                             | -                                 | -               |
| RS 80000 4m     | 80000       | 80        | 4      | -                             | -                                 | -               |
| RS 80000 5m     | 80000       | 80        | 5      | -                             | -                                 | -               |
| RS 100000 4m    | 100000      | 100       | 4      | -                             | -                                 | -               |
| RS 100000 5m    | 100000      | 100       | 5      | -                             | -                                 | -               |



### ORDER NUMBERS[Global Item Number/Local ERP Number SSUK]

| Dimension L1 | 10 t                 | 15 t                   | 20 t                   | 25 t                 | 30 t                 | 40 t                 | 50 t    | 60 t    | 80 t    | 100 t   |
|--------------|----------------------|------------------------|------------------------|----------------------|----------------------|----------------------|---------|---------|---------|---------|
| 1 m          | -                    | -                      | 2024600<br>RS 20000 1m | -                    | -                    | -                    | -       | -       | -       | -       |
| 1.5 m        | 2030407              | -                      | 2024599                | -                    | -                    | -                    | -       | -       | -       | -       |
| 2 m          | 2021021<br>E10000/02 | 2021023<br>E15000/02   | 2021025<br>E20000/02   | 2021027<br>E25000/02 | 2021029<br>E30000/02 | 2021032<br>E40000/02 | -       | -       | -       | -       |
| 3 m          | 2002813<br>E10000/03 | 2002815                | 2002817<br>E20000/03   | 2002819<br>E25000/03 | 2002821<br>E30000/03 | 2002823<br>E40000/03 | 2002825 | -       | -       | -       |
| 4 m          | 2002814<br>E10000/04 | 2002816                | 2002818<br>E20000/04   | 2002820<br>E25000/04 | 2002822<br>E30000/04 | 2002824<br>E40000/04 | 2002826 | 2002827 | 2002829 | 2002831 |
| 5 m          | 2003297<br>E10000/05 | 2003298                | 2003299                | 2003300<br>E25000/05 | -                    | 2003302              | 2003303 | 2002828 | 2002830 | 2002832 |
| 6 m          | 2021022<br>E10000/06 | 2021024<br>E15000/06   | 2021026<br>E20000/06   | 2021028<br>E25000/06 | 2021030<br>E30000/06 | 2021033<br>E40000/06 | -       | -       | -       | -       |
| 8 m          | -                    | 2024862<br>RS 15000 8m | 2024863<br>E20000/08   | 2026435              | -                    | -                    | -       | -       | -       | -       |
| 10 m         | 2029319              | -                      | -                      | 2026436              | -                    | -                    | -       | -       | -       | -       |
| 12 m         | -                    | -                      | -                      | 2027660              | -                    | -                    | -       | -       | -       | -       |
| 15 m         | -                    | -                      | -                      | -                    | 2020566<br>2020566   | -                    | -       | -       | -       | -       |

- Main Material Polyester
- Colour Orange
- Temperature Range - 40 tot + 100°C
- Label Protection Yes
- Packaging Unit (PU) Content 1

1. WLL - working load limit, Nennttragfähigkeit. Gilt für Anschlagart direkt.
2. L1 - Nutzlänge.
3. Abweichend von der DIN EN 1492-2 ist der Werkstoff in dieser Rundschlinge bis zu einer Einsatztemperatur von +70°C geeignet.
4. In der DIN EN 1492-2 ist HMPE als Werkstoff nicht aufgeführt und Materialmischungen sind nicht vorgesehen.

**SpanSet (UK) Limited**  
Telford Way  
Middlewich Cheshire  
CW10 0HX United  
Kingdom  
+44 (0) 1606 737494  
info@spanset.co.uk  
www.spanset.co.uk



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

**SpanSet  
Certified  
Safety**