

## EPIaC kit de sécurité pour échafaudage (101 à 103)

Type de kit de sécurité pour échafaudage

| Nom court de l'article | Harnais | Longe               | Poids net [kg] |
|------------------------|---------|---------------------|----------------|
| SK-101                 | X-2 MS  | SP140 S EL 2m 1RH2  | 3.0            |
| SK-103                 | X-2 QS  | 41-HWB 2,8 1RH2     | 3.1            |
| SK-104                 | X-2 QS  | 41-HWB 2 DWG        | 3.1            |
| SK-102                 | X-2 QS  | SP140 TW EL 2m 1RH2 | 3.86           |



## NUMÉROS DE COMMANDE [Global Item Number/Local ERP Number SSCH]

| Longe                                                                                                  | SK-101            | SK-102            | SK-103            | SK-104            |
|--------------------------------------------------------------------------------------------------------|-------------------|-------------------|-------------------|-------------------|
|  41-HWB 2 DWG         | -                 | -                 | -                 | 2021666<br>SK-104 |
|  SP140 S EL 2m 1RH2  | 2009940<br>SK-101 | -                 | -                 | -                 |
|  SP140 TW EL 2m 1RH2 | -                 | 2009942<br>SK-102 | -                 | -                 |
|  41-HWB 2,8 1RH2      | -                 | -                 | 2009941<br>SK-103 | -                 |

■ Plage de température -40 °F to 120 °F

■ Contenu des unités d'emballage (UE) 1

