

ErgoABS 2000daN 50mm

High tension force with less muscle power with pull-down system together with the safety of the progressive tension release

Item Name short	Lashing Type	Lashing Capacity [daN]	Standard Tension Force [daN]	L2 [m]	L3 [m]	Lashing End Fitting Component
ErgoABS LC2000/50/STF440 2pc 8m DJH	Two-piece	2000	750	0.5	7.5	DJH-50
ErgoABS LC2000/50/STF440 2pc 8m DJHS	Two-piece	2000	750	0.5	7.5	DJHS-50
ErgoABS LC2000/50/STF440 2pc 8m RH	Two-piece	2000	750	0.5	7.5	RH-50
ErgoABS LC2000/50/STF440 2pc 8m SHD	Two-piece	2000	750	0.5	7.5	SHD-50
ErgoABS LC4000/50 1pc 8m	One-piece	4000	350	-	-	No



Lashing Configuration

1-Piece



Lashing Configuration 2-Piece



ORDER NUMBERS[Global Item Number/Local ERP Number SSNL]

Lashing End Fitting Component	ErgoABS LC2000/50/STF440 2pc 8m DJH	ErgoABS LC2000/50/STF440 2pc 8m DJHS	ErgoABS LC2000/50/STF440 2pc 8m RH	ErgoABS LC2000/50/STF440 2pc 8m SHD	ErgoABS LC4000/50 1pc 8m
 No	-	-	-	-	2003009
 DJH-50	2003507	-	-	-	-
 DJHS-50	-	2004018	-	-	-
 RH-50	-	-	2004019	-	-
 SHD-50	-	-	-	2003506	-

■ Norms	EN 12195-2: 2001
■ Surface Coating	Epoxy
■ Webbing Material	Polyester, thermofixed and low-stretch <4%
■ Colour	Blue
■ Webbing Width B	50 mm
■ Webbing Thickness	4 mm
■ Standard Tension Force	350 daN
■ Standard Tension Force (with TFI)	750 daN
■ Anti Belt Slip (ABS)	Yes
■ Tension Force Indicator (TFI)	Yes
■ Label Protection	Yes
■ Handle Type	Long Wide
■ Packaging Unit (PU) Content	1

SpanSet Nederland B.V.
 Plaza 10A 4782 SK
 Moerdijk Nederland
 Tel.: +31 (0) 168 38 68 00
 info@spanset.nl
 www.spanset.nl



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed via electronic systems without the written permission of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Nederland B.V.

**SpanSet
Certified
Safety**