




Lashing Configuration

1-Piece



ErgoABS 2500daN 50mm

High tension force with less muscle power with pull-down system together with the safety of the progressive tension release

Item Name short	Lashing Type	Lashing Capacity [daN]	Standard Tension Force [daN]	L1 [m]	L2 [m]	L3 [m]	Lashing End Fitting Component
ErgoABS LC2500/50 2pc 5.5m 0.5m DJHS	Two-piece	2500	750	6	0.5	5.5	DJHS-50
ErgoABS LC2500/50 2pc 0.5m 7.5m DJH	Two-piece	2500	750	8	0.5	7.5	DJH-50
ErgoABS LC2500/50 2pc 7.5m 0.5m DJHS	Two-piece	2500	750	8	0.5	7.5	DJHS-50
ErgoABS LC2500/50 2pc 7.5m 0.5m RH	Two-piece	2500	750	8	0.5	7.5	RH-50
ErgoABS LC2500/50 2pc 7.5m 0.5m SHD	Two-piece	2500	750	8	0.5	7.5	SHD-50
ErgoABS LC2500/50 2pc 9.5m 0.5m DJHS	Two-piece	2500	750	10	0.5	9.5	DJHS-50
ErgoABS LC5000/50 1pc 8m	One-piece	5000	350	8	-	-	No



Lashing Configuration 2-Piece



ORDER NUMBERS[Global Item Number/Local ERP Number SSNL]

Dimension L1



No



DJH-50



DJHS-50



RH-50



SHD-50

6 m	-	-	2020332	-	-
8 m	2004020	2004022	2004475	2004476	2004021
10 m	-	-	2020333	-	-

■ Norms	EN 12195-2: 2001
■ Surface Coating	Epoxy
■ Webbing Material	Polyester, thermofixed and low-stretch <4%
■ Colour	Blue
■ Webbing Width B	50 mm
■ Webbing Thickness	4 mm
■ Standard Tension Force	350 daN
■ Standard Tension Force (with TFI)	750 daN
■ Anti Belt Slip (ABS)	Yes
■ Tension Force Indicator (TFI)	Yes
■ Label Protection	Yes
■ Handle Type	Long Wide
■ Packaging Unit (PU) Content	1

