




Lashing Configuration

1-Piece



ErgoABS 2500daN 50mm

High tension force with less muscle power with pull-down system together with the safety of the progressive tension release

Item Name short	Lashing Type	Lashing Capacity [daN]	Standard Tension Force [daN]	L1 [m]	L2 [m]	L3 [m]	Lashing End Fitting Component
ErgoABS LC2500/50 2pc 3.5m 0.5m DJHS	Two-piece	2500	750	4	0.5	3.5	DJHS-50
ErgoABS LC2500/50 2pc 5.5m 0.5m DJH	Two-piece	2500	750	6	0.5	5.5	DJH-50
ErgoABS LC2500/50 2pc 0.5m 7.5m DJH	Two-piece	2500	750	8	0.5	7.5	DJH-50
ErgoABS LC2500/50 2pc 7.7m 0.3m DJH	Two-piece	2500	750	8	0.3	7.7	DJH-50
ErgoABS LC2500/50 2pc 7.5m 0.5m DJHS	Two-piece	2500	750	8	0.5	7.5	DJHS-50
ErgoABS LC2500/50 2pc 7.7m 0.3m DJHS	Two-piece	2500	750	8	0.3	7.7	DJHS-50
ErgoABS LC2500/50 2pc 7.7m 0.3m CLR	Two-piece	2500	750	8	0.3	7.7	CLR-50
ErgoABS LC2500/50 2pc 0.5m 9.5m DJH	Two-piece	2500	750	10	0.5	9.5	DJH-50
ErgoABS LC2500/50 2pc 9.7m 0.3m DJH	Two-piece	2500	750	10	0.3	9.7	DJH-50
ErgoABS LC2500/50 2pc 9.5m 0.5m DJHS	Two-piece	2500	750	10	0.5	9.5	DJHS-50
ErgoABS LC2500/50 2pc 9.7m 0.3m DJHS	Two-piece	2500	750	10	0.3	9.7	DJHS-50
ErgoABS LC2500/50 2pc 9.7m 0.3m CLR	Two-piece	2500	750	10	0.3	9.7	CLR-50
ErgoABS LC5000/50 1pc 4m	One-piece	5000	350	4	-	-	No
ErgoABS LC5000/50 1pc 6m	One-piece	5000	350	6	-	-	No
ErgoABS LC5000/50 1pc 10m	One-piece	5000	350	10	-	-	No
ErgoABS LC5000/50 1pc 12m	One-piece	5000	350	12	-	-	No
ErgoABS LC5000/50 1pc 15m	One-piece	5000	350	15	-	-	No



Lashing Configuration 2-Piece



ORDER NUMBERS[Global Item Number/Local ERP Number SSUK]

Dimension L1				
	No	DJH-50	DJHS-50	CLR-50
4 m	2028606	-	2027004 20050-2-01228SL-4M	-
6 m	2026998 20050-1-6MT	2020330 20050-2-01228-6M-050	-	-
8 m	-	2004022 20050-2-01228-8M-050,2024610 20050-2-01228-8M-030	2004475 20050-2-01228SL-8M-050,2024612 20050-2-01288SL-8M-030	2024614 20050-2-CLR-8M-030
10 m	2027001	2020331 20050-2-01228-10M-050,2024611 20050-2-01228-10M-030	2020333 20050-2-01228SL-10M-050,2024613 20050-2-01288SL-10M-030	2024615 20050-2-CLR-10M-030
12 m	2027002	-	-	-
15 m	2027003	-	-	-

■ Norms	EN 12195-2: 2001
■ Surface Coating	Epoxy
■ Webbing Material	Polyester, thermofixed and low-stretch <4%
■ Colour	Blue
■ Webbing Thickness	4 mm
■ Webbing Width B	50 mm
■ Standard Tension Force	350 daN
■ Standard Tension Force (with TFI)	750 daN
■ Anti Belt Slip (ABS)	Yes
■ Tension Force Indicator (TFI)	Yes
■ Label Protection	Yes
■ Handle Type	Long Wide
■ Packaging Unit (PU) Content	1

SpanSet (UK) Limited
Telford Way
Middlewich Cheshire
CW10 0HX United
Kingdom
+44 (0) 1606 737494
info@spanset.co.uk
www.spanset.co.uk



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

**SpanSet
Certified
Safety**