

Exoset - Vertical lifting clamp

Suitable for lifting, vertical transport, turning 180° moving and vertical transfer of sheet, plates and constructions.

Item Name short	WLL t [t]	Jaw Opening Width [mm]	For Material	A [mm]	B [mm]	C [mm]	D [mm]
0.5t EVU	0.5	0 - 16	Normal max.37HRC	39	209	134	40
0.5t EVU/H	0.5	0 - 16	Hard max.47HRC	39	209	134	40
0.5t EVU/S	0.5	0 - 16	Stainless Steel max.37HRC	39	209	134	40
1t EVU/H	1	0 - 20	Hard max.47HRC	39	22	145	52
1t EVU	1	0 - 20	Normal max.37HRC	39	237	145	52
1t EVU/S	1	0 - 20	Stainless Steel max.37HRC	39	237	145	52
2t EVU	2	0 - 35	Normal max.37HRC	68	375	209	76
2t EVU/H	2	0 - 35	Hard max.47HRC	68	375	209	76
2t EVU/S	2	0 - 35	Stainless Steel max.37HRC	68	375	209	76
3t EVU/H	3	0 - 40	Hard max.47HRC	73	446	262	101
3t EVU/S	3	0 - 40	Stainless Steel max.37HRC	73	446	262	101
3t EVU	3	0 - 40	Normal max.37HRC	73	446	262	101
5t EVU	5	0 - 40	Normal max.37HRC	73	446	262	101
5t EVU/H	5	0 - 40	Hard max.47HRC	73	446	262	101
5t EVU/S	5	0 - 40	Stainless Steel max.37HRC	73	446	262	101
6t EVU	6	0 - 50	Normal max.37HRC	80	549	327	131
6t EVU/H	6	0 - 50	Hard max.47HRC	80	549	327	131
6t EVU/S	6	0 - 50	Stainless Steel max.37HRC	80	549	327	131

Item Name short	E [mm]	F [mm]	G [mm]	H [mm]	I [mm]	J [mm]	Weight Net [kg]
0.5t EVU	44	22	123	13	20	28	1.9
0.5t EVU/H	44	22	123	13	20	28	1.9
0.5t EVU/S	44	22	123	13	20	28	1.9
1t EVU/H	46	28	123	13	20	28	2.1
1t EVU	44	28	127	13	20	28	2.1
1t EVU/S	44	28	127	13	20	28	2.1



Item Name short	E [mm]	F [mm]	G [mm]	H [mm]	I [mm]	J [mm]	Weight Net [kg]
2t EVU	61	48	192	18	32	44	7.6
2t EVU/H	61	48	192	18	32	44	7.6
2t EVU/S	61	48	192	18	32	44	7.6
3t EVU/H	71	55	225	22	42	58	14.8
3t EVU/S	71	55	225	22	42	58	14.8
3t EVU	71	55	225	22	42	62	14.8
5t EVU	71	55	225	22	42	62	16
5t EVU/H	71	55	225	22	42	62	16
5t EVU/S	71	55	225	22	42	62	16
6t EVU	97	59	280	37	42	62	24
6t EVU/H	97	59	280	37	42	62	24
6t EVU/S	97	59	280	37	42	62	24



ORDER NUMBERS[Global Item Number/Local ERP Number SSAU]

WLL Vertical	For Material	Jaw Opening Width	0.5 t	1 t	2 t	3 t	5 t	6 t
0 - 0.63 in	Normal max.37HRC	0 - 16 mm	2002421 2002421-EVU-0.5	-	-	-	-	-
0 - 0.63 in	Stainless Steel max.37HRC	0 - 16 mm	2012567	-	-	-	-	-
0 - 0.63 in	Hard max.47HRC	0 - 16 mm	2012561 2012561-EVU-H-0.5	-	-	-	-	-
0 - 0.79 in	Normal max.37HRC	0 - 20 mm	-	2002422	-	-	-	-
0 - 0.79 in	Stainless Steel max.37HRC	0 - 20 mm	-	2012568	-	-	-	-
0 - 0.79 in	Hard max.47HRC	0 - 20 mm	-	2012562 2012562-EVU-H-1	-	-	-	-
0 - 1.38 in	Normal max.37HRC	0 - 35 mm	-	-	2002423	-	-	-
0 - 1.38 in	Stainless Steel max.37HRC	0 - 35 mm	-	-	2012569	-	-	-
0 - 1.38 in	Hard max.47HRC	0 - 35 mm	-	-	2012563 2012563-EVU-H-2	-	-	-
0 - 0.79 in	Normal max.37HRC	0 - 40 mm	-	-	-	2002424	-	-
0 - 1.57 in	Stainless Steel max.37HRC	0 - 40 mm	-	-	-	2012570	-	-
0 - 1.57 in	Hard max.47HRC	0 - 40 mm	-	-	-	2012564	-	-
0 - 1.57 in	Normal max.37HRC	0 - 40 mm	-	-	-	-	2002425	-
0 - 1.57 in	Stainless Steel max.37HRC	0 - 40 mm	-	-	-	-	2012571	-
0 - 1.57 in	Hard max.47HRC	0 - 40 mm	-	-	-	-	2012565 2012565-EVU-H-5	-
0 - 1.97 in	Normal max.37HRC	0 - 50 mm	-	-	-	-	-	2002426
0 - 1.97 in	Stainless Steel max.37HRC	0 - 50 mm	-	-	-	-	-	2012572
0 - 1.97 in	Hard max.47HRC	0 - 50 mm	-	-	-	-	-	2012566

- Standards EN 13155 ASME B30.20 DNV GL
- Packaging Unit (PU) Content 1

SpanSet Australia Ltd
150 Old Bathurst Road
Emu Plains NSW 2750
Australia
+61 (02) 4735 3955
sales@spanset.com.au
www.spanset.com.au



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Australia Ltd

**SpanSet
Certified
Safety**