

Exoset - Vertical lifting clamp

Suitable for lifting, vertical transport, turning 180° moving and vertical transfer of sheet, plates and constructions.

Item Name short	WLL t [t]	Jaw Opening Width [mm]	For Material	A [mm]	B [mm]	C [mm]	D [mm]
0.5t EVU	0.5	0 - 16	Normal max.37HRC	39	209	134	40
0.5t EVU/H	0.5	0 - 16	Hard max.47HRC	39	209	134	40
0.5t EVU/S	0.5	0 - 16	Stainless Steel max.37HRC	39	209	134	40
1t EVU/H	1	0 - 20	Hard max.47HRC	39	22	145	52
1t EVU	1	0 - 20	Normal max.37HRC	39	237	145	52
1t EVU/S	1	0 - 20	Stainless Steel max.37HRC	39	237	145	52
2t EVU	2	0 - 35	Normal max.37HRC	68	375	209	76
2t EVU/H	2	0 - 35	Hard max.47HRC	68	375	209	76
2t EVU/S	2	0 - 35	Stainless Steel max.37HRC	68	375	209	76
3t EVU/H	3	0 - 40	Hard max.47HRC	73	446	262	101
3t EVU/S	3	0 - 40	Stainless Steel max.37HRC	73	446	262	101
3t EVU	3	0 - 40	Normal max.37HRC	73	446	262	101
5t EVU	5	0 - 40	Normal max.37HRC	73	446	262	101
5t EVU/H	5	0 - 40	Hard max.47HRC	73	446	262	101
5t EVU/S	5	0 - 40	Stainless Steel max.37HRC	73	446	262	101
6t EVU	6	0 - 50	Normal max.37HRC	80	549	327	131
6t EVU/H	6	0 - 50	Hard max.47HRC	80	549	327	131
6t EVU/S	6	0 - 50	Stainless Steel max.37HRC	80	549	327	131

Item Name short	E [mm]	F [mm]	G [mm]	H [mm]	I [mm]	J [mm]	Weight Net [kg]
0.5t EVU	44	22	123	13	20	28	1.9
0.5t EVU/H	44	22	123	13	20	28	1.9
0.5t EVU/S	44	22	123	13	20	28	1.9
1t EVU/H	46	28	123	13	20	28	2.1
1t EVU	44	28	127	13	20	28	2.1
1t EVU/S	44	28	127	13	20	28	2.1



Item Name short	E [mm]	F [mm]	G [mm]	H [mm]	I [mm]	J [mm]	Weight Net [kg]
2t EVU	61	48	192	18	32	44	7.6
2t EVU/H	61	48	192	18	32	44	7.6
2t EVU/S	61	48	192	18	32	44	7.6
3t EVU/H	71	55	225	22	42	58	14.8
3t EVU/S	71	55	225	22	42	58	14.8
3t EVU	71	55	225	22	42	62	14.8
5t EVU	71	55	225	22	42	62	16
5t EVU/H	71	55	225	22	42	62	16
5t EVU/S	71	55	225	22	42	62	16
6t EVU	97	59	280	37	42	62	24
6t EVU/H	97	59	280	37	42	62	24
6t EVU/S	97	59	280	37	42	62	24



ORDER NUMBERS[Global Item Number/Local ERP Number SSDE]

WLL Vertical	For Material	Jaw Opening Width	0.5 t	1 t	2 t	3 t	5 t	6 t
0 - 0,63 in	Normal max.37HRC	0 - 16 mm	2002421 D083151X	-	-	-	-	-
0 - 0,63 in	Stainless Steel max.37HRC	0 - 16 mm	2012567 D088438X	-	-	-	-	-
0 - 0,63 in	Hard max.47HRC	0 - 16 mm	2012561 D086132X	-	-	-	-	-
0 - 0,79 in	Normal max.37HRC	0 - 20 mm	-	2002422 D083152X	-	-	-	-
0 - 0,79 in	Stainless Steel max.37HRC	0 - 20 mm	-	2012568 D088439X	-	-	-	-
0 - 0,79 in	Hard max.47HRC	0 - 20 mm	-	2012562 D086046X	-	-	-	-
0 - 1,38 in	Normal max.37HRC	0 - 35 mm	-	-	2002423 D083153X	-	-	-
0 - 1,38 in	Stainless Steel max.37HRC	0 - 35 mm	-	-	2012569 D088440X	-	-	-
0 - 1,38 in	Hard max.47HRC	0 - 35 mm	-	-	2012563 D086133X	-	-	-
0 - 0,79 in	Normal max.37HRC	0 - 40 mm	-	-	-	2002424 D083154X	-	-
0 - 1,57 in	Stainless Steel max.37HRC	0 - 40 mm	-	-	-	2012570 D088441X	-	-
0 - 1,57 in	Hard max.47HRC	0 - 40 mm	-	-	-	2012564 D086134X	-	-
0 - 1,57 in	Normal max.37HRC	0 - 40 mm	-	-	-	-	2002425 D083155X	-
0 - 1,57 in	Stainless Steel max.37HRC	0 - 40 mm	-	-	-	-	2012571 D088442X	-
0 - 1,57 in	Hard max.47HRC	0 - 40 mm	-	-	-	-	2012565 D086142X	-
0 - 1,97 in	Normal max.37HRC	0 - 50 mm	-	-	-	-	-	2002426 D083156X
0 - 1,97 in	Stainless Steel max.37HRC	0 - 50 mm	-	-	-	-	-	2012572 D088444X
0 - 1,97 in	Hard max.47HRC	0 - 50 mm	-	-	-	-	-	2012566 D086144X

■ Norms

EN 13155 ASME B30.20 DNV GL

■ Packaging Unit (PU) Content

1

**SpanSet GmbH & Co.
KG**
Jülicher Straße 49-51
52531 Übach-
Palenberg
Deutschland
+49 (0) 2451 4831-0
info@spanset.de
www.spanset.com



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written authorisation of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. DB040719 © SpanSet GmbH & Co. KG - Germany

**SpanSet
Certified
Safety**