


Exoset Bow Shackle with Screw Collar Pin

Screw pin for quick (dis)assembly

Item Name short	WLL kg [kg]	WLL t [t]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]
BluePin B SCP 1t	1000	1	16.8	11	35.7	9.7	26.2
BluePin B SCP 1.5t	1500	1.5	19	13	42.2	11.2	29.5
BluePin B SCP 2t	2000	2	20.6	16	47.2	12.7	33.1
BluePin B SCP 3.25t	3250	3.25	27	20	60	16	42
BluePin B SCP 4.75t	4750	4.75	31.8	22	71	19	51
BluePin B SCP 6.5t	6500	6.5	36.6	27	84	22	58
BluePin B SCP 8.5t	8500	8.5	43	28.5	95	25	68
BluePin B SCP 9.5t	9500	9.5	46	33	108	28	74
BluePin B SCP 12t	12000	12	51.5	36	119	32	82
BluePin B SCP 13.5t	13500	13.5	57	38	131	35	89
BluePin B SCP 17t	17000	17	60.5	42	148	38	98
BluePin B SCP 25t	25000	25	73	51	177	45	127
BluePin B SCP 35t	35000	35	82.5	57	197	51	146

Item Name short	F [mm]	H [mm]	M [mm]	Weight Net [kg]
BluePin B SCP 1t	23.1	62.2	11	0.15
BluePin B SCP 1.5t	26.9	73.9	13	0.24
BluePin B SCP 2t	30.2	83.5	16	0.4
BluePin B SCP 3.25t	39	106	20	0.60
BluePin B SCP 4.75t	47	125	22	1.0
BluePin B SCP 6.5t	54	147	27	1.50
BluePin B SCP 8.5t	60	166	30	2.35
BluePin B SCP 9.5t	66	185	33	3.20
BluePin B SCP 12t	76	208	36	4.3
BluePin B SCP 13.5t	84	228	-	6.36
BluePin B SCP 17t	92	254	42	7.40
BluePin B SCP 25t	109	303	51	12.8
BluePin B SCP 35t	127	-	57	18.2



ORDER NUMBERS[Global Item Number/Local ERP Number SSDE]

WLL t	BluePin B SCP 1t	BluePin B SCP 1.5t	BluePin B SCP 2t	BluePin B SCP 3.25t	BluePin B SCP 4.75t	BluePin B SCP 6.5t	BluePin B SCP 8.5t	BluePin B SCP 9.5t	BluePin B SCP 12t	BluePin B SCP 13.5t	BluePin B SCP 17t
1 t	2000772	-	-	-	-	-	-	-	-	-	-
1.5 t	-	2000773	-	-	-	-	-	-	-	-	-
2 t	-	-	1058249 D058249	-	-	-	-	-	-	-	-
3.25 t	-	-	-	1058250 D058250	-	-	-	-	-	-	-
4.75 t	-	-	-	-	2000774	-	-	-	-	-	-
6.5 t	-	-	-	-	-	1058269 D058269	-	-	-	-	-
8.5 t	-	-	-	-	-	-	1051713 D058270	-	-	-	-
9.5 t	-	-	-	-	-	-	-	2000776	-	-	-
12 t	-	-	-	-	-	-	-	-	2000777	-	-
13.5 t	-	-	-	-	-	-	-	-	-	1058273 D058273	-
17 t	-	-	-	-	-	-	-	-	-	-	2000779
25 t	-	-	-	-	-	-	-	-	-	-	-
35 t	-	-	-	-	-	-	-	-	-	-	-

WLL t	BluePin B SCP 25t	BluePin B SCP 35t
1 t	-	-
1.5 t	-	-
2 t	-	-
3.25 t	-	-
4.75 t	-	-
6.5 t	-	-
8.5 t	-	-
9.5 t	-	-
12 t	-	-
13.5 t	-	-
17 t	-	-
25 t	2000780 D058275	-
35 t	-	2000781 D040585



■ Norms	EN 13889
■ Grade	50
■ Main Material	Steel
■ Temperature Range	0° C to + 200° C
■ Packaging Unit (PU) Content	1

**SpanSet GmbH & Co.
KG**

Jülicher Straße 49-51
52531 Übach-
Palenberg
Deutschland
+49 (0) 2451 4831-0
info@spanset.de
www.spanset.com



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written authorisation of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. DB040719 © SpanSet GmbH & Co. KG - Germany

**SpanSet
Certified
Safety**