

Exoset Sicherheitshebeklemme

Die perfekte Klemme für den professionellen Gebrauch

Artikel Name kurz	WLL [t]	Greifbereich in mm (min) [mm]	Für Material	A [mm]	B [mm]	C [mm]	D [mm]
0.5t EVU	0.5	0 - 16	Normal max.37HRC	39	209	134	40
0.5t EVU/H	0.5	0 - 16	Hart max.47HRC	39	209	134	40
0.5t EVU/S	0.5	0 - 16	Edelstahl max.37HRC	39	209	134	40
0.5t EVU/J	0.5	15 - 30	Normal max.37HRC	39	226	134	40
1t EVU/H	1	0 - 20	Hart max.47HRC	39	22	145	52
1t EVU	1	0 - 20	Normal max.37HRC	39	237	145	52
1t EVU/S	1	0 - 20	Edelstahl max.37HRC	39	237	145	52
1t EVU/J	1	20 - 40	Normal max.37HRC	39	237	145	52
2t EVU	2	0 - 35	Normal max.37HRC	68	375	209	76
2t EVU/H	2	0 - 35	Hart max.47HRC	68	375	209	76
2t EVU/S	2	0 - 35	Edelstahl max.37HRC	68	375	209	76
2t EVU/J	2	35 - 70	Normal max.37HRC	68	375	209	76
3t EVU/H	3	0 - 40	Hart max.47HRC	73	446	262	101
3t EVU/S	3	0 - 40	Edelstahl max.37HRC	73	446	262	101
3t EVU	3	0 - 40	Normal max.37HRC	73	446	262	101
3t EVU/J	3	40 - 80	Normal max.37HRC	73	446	262	101
5t EVU	5	0 - 40	Normal max.37HRC	73	446	262	101
5t EVU/H	5	0 - 40	Hart max.47HRC	73	446	262	101
5t EVU/S	5	0 - 40	Edelstahl max.37HRC	73	446	262	101
5t EVU/J	5	40 - 80	Normal max.37HRC	73	446	262	101
6t EVU	6	0 - 50	Normal max.37HRC	80	549	327	131
6t EVU/H	6	0 - 50	Hart max.47HRC	80	549	327	131



Artikel Name kurz	WLL [t]	Greifbereich in mm (min) [mm]	Für Material	A [mm]	B [mm]	C [mm]	D [mm]
6t EVU/S	6	0 - 50	Edelstahl max.37HRC	80	549	327	131
6t EVU/J	6	50 - 100	Normal max.37HRC	80	549	327	131

Artikel Name kurz	E [mm]	F [mm]	G [mm]	H [mm]	I [mm]	J [mm]	Nettogewicht kg [kg]
0.5t EVU	44	22	123	13	20	28	1.9
0.5t EVU/H	44	22	123	13	20	28	1.9
0.5t EVU/S	44	22	123	13	20	28	1.9
0.5t EVU/J	41	41	125	13	20	28	2.0
1t EVU/H	46	28	123	13	20	28	2.1
1t EVU	44	28	127	13	20	28	2.1
1t EVU/S	44	28	127	13	20	28	2.1
1t EVU/J	44	51	145	13	20	28	2.6
2t EVU	61	48	192	18	32	44	7.6
2t EVU/H	61	48	192	18	32	44	7.6
2t EVU/S	61	48	192	18	32	44	7.6
2t EVU/J	61	87	225	18	32	44	8.9
3t EVU/H	71	55	225	22	42	58	14.8
3t EVU/S	71	55	225	22	42	58	14.8
3t EVU	71	55	225	22	42	62	14.8
3t EVU/J	71	100	265	22	42	58	13.7
5t EVU	71	55	225	22	42	62	16
5t EVU/H	71	55	225	22	42	62	16
5t EVU/S	71	55	225	22	42	62	16
5t EVU/J	71	100	265	22	42	62	16.4
6t EVU	97	59	280	37	42	62	24
6t EVU/H	97	59	280	37	42	62	24
6t EVU/S	97	59	280	37	42	62	24
6t EVU/J	97	114	330	37	42	62	24.9



BESTELLNUMMERN[Global Item Number/Local ERP Number SSCH]

WLL Vertikal	Für Material	Greifbereich in mm (min)	Greifbereich in mm (min)	0.5 t	1 t	2 t	3 t	5 t	6 t
1100 lbs	Normal max.37HRC	0 - 16 mm	0 - 0.63 in	2002421 EVU05	-	-	-	-	-
1100 lbs	Normal max.37HRC	15 - 30 mm	0.59 - 1.18 in	2030330 EVU05J	-	-	-	-	-
1100 lbs	Edelstahl max.37HRC	0 - 16 mm	0 - 0.63 in	2012567 EVUS05	-	-	-	-	-
1100 lbs	Hart max.47HRC	0 - 16 mm	0 - 0.63 in	2012561 EVUH05	-	-	-	-	-
2204 lbs	Normal max.37HRC	0 - 20 mm	0 - 0.79 in	-	2002422 EVU1	-	-	-	-
2204 lbs	Normal max.37HRC	20 - 40 mm	0.79 - 2.75 in	-	2030331 EVU1J	-	-	-	-
2204 lbs	Edelstahl max.37HRC	0 - 20 mm	0 - 0.79 in	-	2012568 EVUS1	-	-	-	-
2204 lbs	Hart max.47HRC	0 - 20 mm	0 - 0.79 in	-	2012562 EVUH1	-	-	-	-
4409 lbs	Normal max.37HRC	0 - 35 mm	0 - 1.38 in	-	-	2002423 EVU2	-	-	-
4409 lbs	Normal max.37HRC	35 - 70 mm	1.38 - 2.75 in	-	-	2030332 EVU2J	-	-	-
4409 lbs	Edelstahl max.37HRC	0 - 35 mm	0 - 1.38 in	-	-	2012569 EVUS2	-	-	-
4409 lbs	Hart max.47HRC	0 - 35 mm	0 - 1.38 in	-	-	2012563 EVUH2	-	-	-
6613 lbs	Normal max.37HRC	0 - 40 mm	0 - 0.79 in	-	-	-	2002424 EVU3	-	-
6613 lbs	Normal max.37HRC	40 - 80 mm	1.57 - 3.15 in	-	-	-	2030333 EVU3J	-	-
6613 lbs	Edelstahl max.37HRC	0 - 40 mm	0 - 1.57 in	-	-	-	2012570 EVUS3	-	-
6613 lbs	Hart max.47HRC	0 - 40 mm	0 - 1.57 in	-	-	-	2012564 EVUH3	-	-
11023 lbs	Normal max.37HRC	0 - 40 mm	0 - 1.57 in	-	-	-	-	2002425 EVU5	-
11023 lbs	Normal max.37HRC	40 - 80 mm	1.57 - 3.15 in	-	-	-	-	2030334 EVU5J	-
11023 lbs	Edelstahl max.37HRC	0 - 40 mm	0 - 1.57 in	-	-	-	-	2012571 EVUS5	-
11023 lbs	Hart max.47HRC	0 - 40 mm	0 - 1.57 in	-	-	-	-	2012565 EVUH5	-
13227 lbs	Normal max.37HRC	0 - 50 mm	0 - 1.97 in	-	-	-	-	-	2002426
13227 lbs	Normal max.37HRC	50 - 100 mm	1.97 - 3.94 in	-	-	-	-	-	2030335 EVU6J



WLL Vertikal	Für Material	Greifbereich in mm (min)	Greifbereich in mm (min)	0.5 t	1 t	2 t	3 t	5 t	6 t
13227 lbs	Edelstahl max.37HRC	0 - 50 mm	0 - 1.97 in	-	-	-	-	-	2012572
13227 lbs	Hart max.47HRC	0 - 50 mm	0 - 1.97 in	-	-	-	-	-	2012566

- Normen EN 13155 ASME B30.20 DNV GL
- Verpackungseinheit (VPE) Inhalt 1

