

Flat Sling 2ply Eco

Standard Flat sling for rough working conditions



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Weight for 1m [kg]
WS Eco 2ply 500 2m	500.00	0.5	2	1	36	3.0	0.2
WS Eco 2ply 500 3m	500.00	0.5	3	1	36	3.0	0.2
WS Eco 2ply 500 4m	500.00	0.5	4	1	36	3.0	0.2
WS Eco 2ply 500 5m	500.00	0.5	5	1	36	3.0	0.2
WS Eco 2ply 500 6m	500.00	0.5	6	1	36	3.0	0.2
WS Eco 2ply 500 8m	500	0.5	8	1	36	3.0	0.2
WS Eco 2ply 1000 2m	1000	1	2	0.2	30	5.2	-
WS Eco 2ply 1000 3m	1000	1	3	0.2	30	5.2	-
WS Eco 2ply 1000 4m	1000.00	1	4	0.2	30	5.2	-
WS Eco 2ply 1000 5m	1000	1	5	0.2	30	5.2	-
WS Eco 2ply 1000 6m	1000	1	6	0.2	30	5.2	-
WS Eco 2ply 1000 8m	1000	1	8	0.2	30	5.2	-
WS Eco 2ply 1500 2m	1500.00	1.5	2	1	50	6.8	0.4
WS Eco 2ply 1500 3m	1500.00	1.5	3	1	50	6.8	0.4
WS Eco 2ply 1500 4m	1500.00	1.5	4	1	50	6.8	0.4
WS Eco 2ply 1500 5m	1500.00	1.5	5	1	50	6.8	0.4
WS Eco 2ply 1500 6m	1500.00	1.5	6	1	50	6.8	0.4
WS Eco 2ply 1500 8m	1500.00	1.5	8	1	50	6.8	0.4
WS Eco 2ply 2000 2m	2000	2	2	0	60	5.0	0.6



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Weight for 1m [kg]
WS Eco 2ply 2000 3m	2000	2	3	0	60	5.0	0.6
WS Eco 2ply 2000 4m	2000	2	4	0	60	5.0	0.6
WS Eco 2ply 2000 5m	2000	2	5	0	60	5.0	0.6
WS Eco 2ply 2000 6m	2000	2	6	0	60	5.0	0.6
WS Eco 2ply 2000 8m	2000	2	8	0	60	5.0	0.6
WS Eco 2ply 3000 2m	3000	3	2	1.5	90	5.0	0.6
WS Eco 2ply 3000 3m	3000	3	3	1.5	90	5.0	0.6
WS Eco 2ply 3000 4m	3000	3	4	1.5	90	5.0	0.6
WS Eco 2ply 3000 5m	3000	3	5	1.5	90	5.0	0.6
WS Eco 2ply 3000 6m	3000	3	6	1.5	90	5.0	0.6
WS Eco 2ply 3000 8m	3000	3	8	1.5	90	5.0	0.6
WS Eco 2ply 4000 2m	4000	4	2	1.5	120	6.8	0.9
WS Eco 2ply 4000 3m	4000	4	3	1.5	120	6.8	0.9
WS Eco 2ply 4000 4m	4000	4	4	1.5	120	6.8	0.9
WS Eco 2ply 4000 5m	4000	4	5	1.5	120	6.8	0.9
WS Eco 2ply 4000 6m	4000	4	6	1.5	120	6.8	0.9
WS Eco 2ply 4000 8m	4000	4	8	1.5	120	6.8	0.9
WS Eco 2ply 5000 2m	5000	5	2	1.7	150	6.6	1.2
WS Eco 2ply 5000 3m	5000	5	3	1.7	150	6.6	1.2
WS Eco 2ply 5000 4m	5000	5	4	1.7	150	6.6	1.2



Item Name short	WLL kg [kg]	WLL t [t]	L1 [m]	L1 min. [m]	Webbing Width B [mm]	Webbing Thickness [mm]	Weight for 1m [kg]
WS Eco 2ply 5000 5m	5000.00	5	5	1.7	150	6.6	1.2
WS Eco 2ply 5000 6m	5000	5	6	1.7	150	6.6	1.2
WS Eco 2ply 5000 8m	5000	5	8	1.7	150	6.6	1.2
WS Eco 2ply 6000 2m	6000	6	2	2.1	180	7.2	1.4
WS Eco 2ply 6000 3m	6000	6	3	2.1	180	7.2	1.4
WS Eco 2ply 6000 4m	6000	6	4	2.1	180	7.2	1.4
WS Eco 2ply 6000 5m	6000	6	5	2.1	180	7.2	1.4
WS Eco 2ply 6000 6m	6000	6	6	2.1	180	7.2	1.4
WS Eco 2ply 6000 8m	6000	6	8	2.1	180	7.2	1.4
WS Eco 2ply 8000 2m	8000.00	8	2	2.3	240	7.2	1.8
WS Eco 2ply 8000 3m	8000.00	8	3	2.3	240	7.2	1.8
WS Eco 2ply 8000 4m	8000.00	8	4	2.3	240	7.2	1.8
WS Eco 2ply 8000 5m	8000.00	8	5	2.3	240	7.2	1.8
WS Eco 2ply 8000 6m	8000.00	8	6	2.3	240	7.2	1.8
WS Eco 2ply 8000 8m	8000.00	8	8	2.3	240	7.2	1.8
WS Eco 2ply 10000 3m	10000.00	10	3	2.6	300	7.4	2.4
WS Eco 2ply 10000 4m	10000.00	10	4	2.6	300	7.4	2.4
WS Eco 2ply 10000 5m	10000.00	10	5	2.6	300	7.4	2.4
WS Eco 2ply 10000 6m	10000.00	10	6	2.6	300	7.4	2.4
WS Eco 2ply 10000 8m	10000.00	10	8	2.6	300	7.4	2.4



Item Name short	Colour
WS Eco 2ply 500 2m	-
WS Eco 2ply 500 3m	-
WS Eco 2ply 500 4m	-
WS Eco 2ply 500 5m	-
WS Eco 2ply 500 6m	-
WS Eco 2ply 500 8m	-
WS Eco 2ply 1000 2m	Purple
WS Eco 2ply 1000 3m	Purple
WS Eco 2ply 1000 4m	Purple
WS Eco 2ply 1000 5m	Purple
WS Eco 2ply 1000 6m	Purple
WS Eco 2ply 1000 8m	Purple
WS Eco 2ply 1500 2m	Olive
WS Eco 2ply 1500 3m	Olive
WS Eco 2ply 1500 4m	Olive
WS Eco 2ply 1500 5m	Olive
WS Eco 2ply 1500 6m	Olive
WS Eco 2ply 1500 8m	Olive
WS Eco 2ply 2000 2m	Green
WS Eco 2ply 2000 3m	Green
WS Eco 2ply 2000 4m	Green
WS Eco 2ply 2000 5m	Green
WS Eco 2ply 2000 6m	Green
WS Eco 2ply 2000 8m	Green
WS Eco 2ply 3000 2m	Yellow
WS Eco 2ply 3000 3m	Yellow
WS Eco 2ply 3000 4m	Yellow
WS Eco 2ply 3000 5m	Yellow



Item Name short	Colour
WS Eco 2ply 3000 6m	Yellow
WS Eco 2ply 3000 8m	Yellow
WS Eco 2ply 4000 2m	Grey
WS Eco 2ply 4000 3m	Grey
WS Eco 2ply 4000 4m	Grey
WS Eco 2ply 4000 5m	Grey
WS Eco 2ply 4000 6m	Grey
WS Eco 2ply 4000 8m	Grey
WS Eco 2ply 5000 2m	Red
WS Eco 2ply 5000 3m	Red
WS Eco 2ply 5000 4m	Red
WS Eco 2ply 5000 5m	Red
WS Eco 2ply 5000 6m	Red
WS Eco 2ply 5000 8m	Red
WS Eco 2ply 6000 2m	Grey
WS Eco 2ply 6000 3m	Grey
WS Eco 2ply 6000 4m	Grey
WS Eco 2ply 6000 5m	Grey
WS Eco 2ply 6000 6m	Grey
WS Eco 2ply 6000 8m	Grey
WS Eco 2ply 8000 2m	Blue
WS Eco 2ply 8000 3m	Blue
WS Eco 2ply 8000 4m	Blue
WS Eco 2ply 8000 5m	Blue
WS Eco 2ply 8000 6m	Blue
WS Eco 2ply 8000 8m	Blue
WS Eco 2ply 10000 3m	Orange



Item Name short

Colour

WS Eco 2ply 10000 4m

Orange

WS Eco 2ply 10000 5m

Orange

WS Eco 2ply 10000 6m

Orange

WS Eco 2ply 10000 8m

Orange

ORDER NUMBERS[Global Item Number/Local ERP Number SSNL]

WLL kg	2 m	3 m	4 m	5 m	6 m	8 m
500.00 kg	2002924	2002925	2003385	2003840	2003841	-
500 kg	-	-	-	-	-	2003842
1000 kg	2002926	2002927	-	-	-	-
1000.00 kg	-	-	2003386	-	-	-
1000 kg	-	-	-	2003843	2003844	2003845
1500.00 kg	2002928	2002929	2003387	2003846	2003847	2003848
2000 kg	2002930	2002931	2003388	2003849	2003850	2003851
3000 kg	2002932	2002933	2003389	2003852	2003853	2003854
4000 kg	2002934	2002935	2003390	2003855	2003856	2003857
5000 kg	2002936	2002937	2003391	-	-	-
5000.00 kg	-	-	-	2003858	-	-
5000 kg	-	-	-	-	2003859	2003860
6000 kg	2002938	2002939	2003392	2003861	2003862	2003863
8000.00 kg	2002940	2002941	2003393	2003864	2003865	2003866
10000.00 kg	-	2002943	2003394	2003867	2003868	2003869

- Main Material Polyester
- Temperature Range -40°C to +100°C
- Packaging Unit (PU) Content 1

SpanSet Nederland B.V.
 Plaza 10A 4782 SK
 Moerdijk Nederland
 Tel.: +31 (0) 168 38 68 00
 info@spanset.nl
 www.spanset.nl



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed via electronic systems without the written permission of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Nederland B.V.

**SpanSet
 Certified
 Safety**