



Flexi Anchor

The Flexi Anchor is an easy-to-use anchoring solution for structural elements. Lightweight, flexible, and with a minimum breaking strength of 22 kN.

Item Name short	Length [mm]	Weight Net [kg]
FLEXI ANCHOR	-	-
FLEXI ANCHOR-0,6M	600	0.65
FLEXI ANCHOR-0,8M	800	0.68
FLEXI ANCHOR-1M	1000	0.7
FLEXI ANCHOR-1,2M	1200	0.74
FLEXI ANCHOR-1,5M	1500	0.8
FLEXI ANCHOR-2M	2000	0.9

ORDER NUMBERS[Global Item Number/Local ERP Number SSID]

Length	FLEXI ANCHOR	FLEXI ANCHOR-0,6M	FLEXI ANCHOR-0,8M	FLEXI ANCHOR-1M	FLEXI ANCHOR-1,2M	FLEXI ANCHOR-1,5M	FLEXI ANCHOR-2M
-	2028212	-	-	-	-	-	-
600 mm	-	2027726 FLEXI ANCHOR-0,6M	-	-	-	-	-
800 mm	-	-	2027727 FLEXI ANCHOR-0,8M	-	-	-	-
1'000 mm	-	-	-	2027728 FLEXI ANCHOR-1M	-	-	-
1'200 mm	-	-	-	-	2028153 FLEXI ANCHOR-1,2M	-	-
1'500 mm	-	-	-	-	-	2028141 FLEXI ANCHOR-1,5M	-
2'000 mm	-	-	-	-	-	-	2028142 FLEXI ANCHOR-2M

■ Norms	EN 566: 2017
■ Main Material	Polyester
■ Packaging Unit (PU) Content	1

SpanSet Indonesia
Marunda Center Blok
F No.20 Segara
Makmur, Tarumajaya.
Bekasi, Indonesia.
17211
+62 21 285 100 77
sales@spanset.co.id
www.spanset.co.id



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Indonesia - Indonesia

**SpanSet
Certified
Safety**