


Gancho de ojal con cierre automático

Gancho para elevación de 1,5 t a 10 t



Nombre corto del Item	CMU [kg]	Diámetro de la cadena	CMU [t]	A [mm]	B [mm]	D [mm]	I [mm]
ESLH-6-10	1400	6 mm	1.4	108	70	20	21
ESLH-8-10	2500	8 mm	2.5	135	90	26	27
ESLH-10-10	4000	10 mm	4	165	108	30	34.5
ESLH-13-10	6700	13 mm	6.7	205	138.5	40.5	40
ESLH-16-10	10000	16 mm	10	255	170.5	50.5	50

Nombre corto del Item	K [mm]	L [mm]	O [mm]	Peso Neto [kg]
ESLH-6-10	43	141	28	0.5
ESLH-8-10	51	175	35.5	0.9
ESLH-10-10	64.3	212.5	45	1.5
ESLH-13-10	80	270	53.5	2.7
ESLH-16-10	104	331	62	5.7



REFERENCIAS DE PEDIDO[Global Item Number/Local ERP Number SSES]

Díámetro de la cadena	ESLH-6-10	ESLH-8-10	ESLH-10-10	ESLH-13-10	ESLH-16-10
6 mm	2018566 C11ESLH00601420	-	-	-	-
8 mm	-	2018567 C11ESLH00801420	-	-	-
10 mm	-	-	2018568 C11ESLH01001420	-	-
13 mm	-	-	-	2018569 C11ESLH01301420	-
16 mm	-	-	-	-	2018570 C11ESLH01601420

- Normas EN 1677
- Grado 100
- Material principal Acero
- Color Azul
- Rango de temperatura -40°C / 200°C
- Rango de temperatura -40°F / 120°F
- Unidad de embalaje (PU) Contiene 1

