



Grip-S

Higher friction reduce the size and or number of lashings required, potentially making loading and unloading faster

Item Name short	Length [mm]	Width [mm]	Thickness [mm]	Weight Net [kg]
Grip-S L 0.20m B 0.20m H 2mm	200	200	2	0.12
Grip-S L 5m B 0.26m H 2mm	5000	266	2	3.86
Grip-S L 5m B 0.26m H 9.53mm	5000	266	9.53	15
Grip-S L 5m B 0.109m H 2mm	5000	1092	2	17.48
Grip-S L 5m B 1.25m H 9.53mm	5000	1250	9.53	63.5
Grip-S L 20m B 0.15m H 2mm	20000	150	2	9.82

ORDER NUMBERS[Global Item Number/Local ERP Number SSDE]

Width	Length	2 mm	9.53 mm
150 mm	20'000 mm	2006042 D000173	-
200 mm	200 mm	2006040 D000165	-
266 mm	5'000 mm	2006041 D000167	2006044 D000168
1'092 mm	5'000 mm	2017039 D000166	-
1'250 mm	5'000 mm	-	2017040 D009001

- Colour Black
- Temperature Range -40° C to + 100° C
- Packaging Unit (PU) Content 1

SpanSet GmbH & Co. KG
Jülicher Straße 49-51
52531 Übach-
Palenberg
Deutschland
+49 (0) 2451 4831-0
info@spanset.de
www.spanset.com



Subject to technical changes. All rights reserved. No part of this technical data sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written authorisation of SpanSet. This technical data sheet has been compiled with due care; SpanSet accepts no liability for errors or omissions. DB040719 © SpanSet GmbH & Co. KG - Germany

**SpanSet
Certified
Safety**