




Hyflex 6x29Fi LHOL

General Purpose Ropes 6 & 8 Strands Conventional Products

Item Name short	Rope Diameter [mm]	Minimum Breaking Force [Kn] [kN]	Minimum Breaking Force [Tn] [t]
HYFLEX 6X29 10MM LHOL	10	69.8	7.1
HYFLEX 6X29 14MM LHOL	14	137	14
HYFLEX 6X29 16MM LHOL	16	179	18.3
HYFLEX 6X29 18MM LHOL	18	226	23
HYFLEX 6X29 20MM LHOL	20	279	28.4
HYFLEX 6X29 28MM LHOL	28	547	55.8
HYFLEX 6X29 40MM LHOL	40	1120	114
HYFLEX 6X29 56MM LHOL	56	2190	256
HYFLEX 6X29 60MM LHOL	-	2510	256



ORDER NUMBERS[Global Item Number/Local ERP Number SSID]

Rope Diameter	HYFLEX 6X29 10MM LHOL	HYFLEX 6X29 14MM LHOL	HYFLEX 6X29 16MM LHOL	HYFLEX 6X29 18MM LHOL	HYFLEX 6X29 20MM LHOL	HYFLEX 6X29 28MM LHOL	HYFLEX 6X29 40MM LHOL	HYFLEX 6X29 56MM LHOL	HYFLEX 6X29 60MM LHOL
-	-	-	-	-	-	-	-	-	2023925 UM6X2900- IWd60.0ZS1960G
10 mm	2023901 UM6X2900- IWd10.0ZS1960G	-	-	-	-	-	-	-	-
14 mm	-	2023904 UM6X2900- IWd14.0ZS1960G	-	-	-	-	-	-	-
16 mm	-	-	2023905 UM6X2900- IWd16.0ZS1960G	-	-	-	-	-	-
18 mm	-	-	-	2023906 UM6X2900- IWd18.0ZS1960G	-	-	-	-	-
20 mm	-	-	-	-	2023907 UM6X2900- IWd20.0ZS1960G	-	-	-	-
28 mm	-	-	-	-	-	2023910 UM6X2900- IWd28.0ZS1960G	-	-	-
40 mm	-	-	-	-	-	-	2023918 UM6X2900- IWd40.0ZS1960G	-	-
56 mm	-	-	-	-	-	-	-	2023924 UM6X2900- IWd56.0ZS1960G	-

- Main Material Steel
- Temperature Range -40° C to + 100° C
- Packaging Unit (PU) Content 1

SpanSet Indonesia
Marunda Center Blok
F No.20 Segara
Makmur, Tarumajaya.
Bekasi, Indonesia.
17211
+62 21 285 100 77
sales@spanset.co.id
www.spanset.co.id



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Indonesia - Indonesia

**SpanSet
Certified
Safety**