



Hyflex 6x29Fi RHOL

General Purpose Ropes 6 & 8 Strands Conventional Products

Item Name short	Rope Diameter [mm]	Minimum Breaking Force [Kn] [kN]	Minimum Breaking Force [Tn] [t]
HYFLEX 6X29 10MM RHOL	10	69.8	7.1
HYFLEX 6X29 14MM RHOL	14	137	14
HYFLEX 6X29 16MM RHOL	16	179	18.3
HYFLEX 6X29 18MM RHOL	18	226	23
HYFLEX 6X29 20MM RHOL	20	279	28.4
HYFLEX 6X29 28MM RHOL	28	547	55.8
HYFLEX 6X29 40MM RHOL	40	1120	114
HYFLEX 6X29 56MM RHOL	56	2190	223
HYFLEX 6X29 60MM RHOL	60	2510	256



ORDER NUMBERS[Global Item Number/Local ERP Number SSID]

Rope Diameter	HYFLEX 6X29 10MM RHOL	HYFLEX 6X29 14MM RHOL	HYFLEX 6X29 16MM RHOL	HYFLEX 6X29 18MM RHOL	HYFLEX 6X29 20MM RHOL	HYFLEX 6X29 28MM RHOL	HYFLEX 6X29 40MM RHOL	HYFLEX 6X29 56MM RHOL	HYFLEX 6X29 60MM RHOL
10 mm	2023878 UM6X2900- IWd10.0SZ1960G	-	-	-	-	-	-	-	-
14 mm	-	2023881 UM6X2900- IWd14.0SZ1960G	-	-	-	-	-	-	-
16 mm	-	-	2023882 UM6X2900- IWd16.0SZ1960G	-	-	-	-	-	-
18 mm	-	-	-	2023883 UM6X2900- IWd18.0SZ1960G	-	-	-	-	-
20 mm	-	-	-	-	2023884 UM6X2900- IWd20.0SZ1960G	-	-	-	-
28 mm	-	-	-	-	-	2023887 UM6X2900- IWd28.0SZ1960G	-	-	-
40 mm	-	-	-	-	-	-	2023893 UM6X2900- IWd40.0SZ1960G	-	-
56 mm	-	-	-	-	-	-	-	2023899 UM6X2900- IWd56.0SZ1960G	-
60 mm	-	-	-	-	-	-	-	-	2023900 UM6X2900- IWd60.0SZ1960G

- Main Material Steel
- Temperature Range -40° C to + 100° C
- Packaging Unit (PU) Content 1

SpanSet Indonesia
Marunda Center Blok
F No.20 Segara
Makmur, Tarumajaya.
Bekasi, Indonesia.
17211
+62 21 285 100 77
sales@spanset.co.id
www.spanset.co.id



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet Indonesia - Indonesia

**SpanSet
Certified
Safety**