




Hyflex 8P RHOL

Tali Serbaguna 6 & 8 Strand Produk Konvensional

Item Name short	Rope Diameter [mm]	Minimum Breaking Force [Kn]	Minimum Breaking Force [Tn]
HYFLEX 8X26 10MM Pi RHOL	10	72.9	7.4
HYFLEX 8X26 11MM Pi RHOL	11	86.1	8.8
HYFLEX 8X26 12MM Pi RHOL	12	105	10.7
HYFLEX 8X26 13MM Pi RHOL	13	124	12.6
HYFLEX 8X26 14MM Pi RHOL	14	143	14.6
HYFLEX 8X26 15MM Pi RHOL	15	164	16.7
HYFLEX 8X26 16MM Pi RHOL	16	187	19.1
HYFLEX 8X26 17MM Pi RHOL	17	211	21.5
HYFLEX 8X26 18MM Pi RHOL	18	239	24.4
HYFLEX 8X26 19MM Pi RHOL	19	269	27.4
HYFLEX 8X26 20MM Pi RHOL	20	295	30.1
HYFLEX 8X26 22MM Pi RHOL	22	356	36.3
HYFLEX 8X26 24MM Pi RHOL	24	423	43.1
HYFLEX 8X26 26MM Pi RHOL	26	500	51
HYFLEX 8X26 28MM Pi RHOL	28	572	58.3
HYFLEX 8X26 30MM Pi RHOL	30	-	-
HYFLEX 8X26 32MM Pi RHOL	32	747	76.1
HYFLEX 8X26 34MM Pi RHOL	34	843	85.9
HYFLEX 8X26 36MM Pi RHOL	36	935	95.3
HYFLEX 8X26 38MM Pi RHOL	38	1043	106



Item Name short	Rope Diameter [mm]	Minimum Breaking Force [Kn] [kN]	Minimum Breaking Force [Tn] [t]
HYFLEX 8X26 40MM Pi RHOL	40	1162	118
HYFLEX 8X26 42MM Pi RHOL	42	1305	133
HYFLEX 8X26 44MM Pi RHOL	44	1412	144
HYFLEX 8X26 46MM Pi RHOL	46	1543	157
HYFLEX 8X26 48MM Pi RHOL	48	1680	171
HYFLEX 8X26 50MM Pi RHOL	50	1833	187
HYFLEX 8X26 52MM Pi RHOL	52	1972	201



NOMOR PESANAN[Global Item Number/Local ERP Number SSID]

Rope Diameter	HYFLEX 8X26 10MM Pi RHOL	HYFLEX 8X26 11MM Pi RHOL	HYFLEX 8X26 12MM Pi RHOL	HYFLEX 8X26 13MM Pi RHOL	HYFLEX 8X26 14MM Pi RHOL	HYFLEX 8X26 15MM Pi RHOL	HYFLEX 8X26 16MM Pi RHOL	HYFLEX 8X26 17MM Pi RHOL	HYFLEX 8X26 18MM Pi RHOL	HYFLEX 8X26 19MM Pi RHOL
10 mm	2023748 UM8X26OP- IWd10.0SZ1960G	-	-	-	-	-	-	-	-	-
11 mm	-	2023749 UM8X26OP- IWd11.0SZ1960G	-	-	-	-	-	-	-	-
12 mm	-	-	2023750 UM8X26OP- IWd12.0SZ1960G	-	-	-	-	-	-	-
13 mm	-	-	-	2023751 UM8X26OP- IWd13.0SZ1960G	-	-	-	-	-	-
14 mm	-	-	-	-	2023752 UM8X26OP- IWd14.0SZ1960G	-	-	-	-	-
15 mm	-	-	-	-	-	2023753 UM8X26OP- IWd15.0SZ1960G	-	-	-	-
16 mm	-	-	-	-	-	-	2023754 UM8X26OP- IWd16.0SZ1960G	-	-	-
17 mm	-	-	-	-	-	-	-	2023755 UM8X26OP- IWd17.0SZ1960G	-	-
18 mm	-	-	-	-	-	-	-	-	2023756 UM8X26OP- IWd18.0SZ1960G	-
19 mm	-	-	-	-	-	-	-	-	-	2023757 UM8X26OP- IWd19.0SZ1960G
20 mm	-	-	-	-	-	-	-	-	-	-
22 mm	-	-	-	-	-	-	-	-	-	-
24 mm	-	-	-	-	-	-	-	-	-	-
26 mm	-	-	-	-	-	-	-	-	-	-
28 mm	-	-	-	-	-	-	-	-	-	-
30 mm	-	-	-	-	-	-	-	-	-	-
32 mm	-	-	-	-	-	-	-	-	-	-
34 mm	-	-	-	-	-	-	-	-	-	-
36 mm	-	-	-	-	-	-	-	-	-	-



Rope Diameter	HYFLEX 8X26 10MM Pi RHOL	HYFLEX 8X26 11MM Pi RHOL	HYFLEX 8X26 12MM Pi RHOL	HYFLEX 8X26 13MM Pi RHOL	HYFLEX 8X26 14MM Pi RHOL	HYFLEX 8X26 15MM Pi RHOL	HYFLEX 8X26 16MM Pi RHOL	HYFLEX 8X26 17MM Pi RHOL	HYFLEX 8X26 18MM Pi RHOL	HYFLEX 8X26 19MM Pi RHOL
38 mm	-	-	-	-	-	-	-	-	-	-
40 mm	-	-	-	-	-	-	-	-	-	-
42 mm	-	-	-	-	-	-	-	-	-	-
44 mm	-	-	-	-	-	-	-	-	-	-
46 mm	-	-	-	-	-	-	-	-	-	-
48 mm	-	-	-	-	-	-	-	-	-	-
50 mm	-	-	-	-	-	-	-	-	-	-
52 mm	-	-	-	-	-	-	-	-	-	-

Rope Diameter	HYFLEX 8X26 22MM Pi RHOL	HYFLEX 8X26 24MM Pi RHOL	HYFLEX 8X26 26MM Pi RHOL	HYFLEX 8X26 28MM Pi RHOL	HYFLEX 8X26 30MM Pi RHOL	HYFLEX 8X26 32MM Pi RHOL	HYFLEX 8X26 34MM Pi RHOL	HYFLEX 8X26 36MM Pi RHOL	HYFLEX 8X26 38MM Pi RHOL	HYFLEX 8X26 40MM Pi RHOL
10 mm	-	-	-	-	-	-	-	-	-	-
11 mm	-	-	-	-	-	-	-	-	-	-
12 mm	-	-	-	-	-	-	-	-	-	-
13 mm	-	-	-	-	-	-	-	-	-	-
14 mm	-	-	-	-	-	-	-	-	-	-
15 mm	-	-	-	-	-	-	-	-	-	-
16 mm	-	-	-	-	-	-	-	-	-	-
17 mm	-	-	-	-	-	-	-	-	-	-
18 mm	-	-	-	-	-	-	-	-	-	-
19 mm	-	-	-	-	-	-	-	-	-	-
20 mm	-	-	-	-	-	-	-	-	-	-
22 mm	2023759 UM8X26OP- IWD22.0SZ1960G									
24 mm	2023760 UM8X26OP- IWD24.0SZ1960G									
26 mm	2023761 UM8X26OP- IWD26.0SZ1960G									
28 mm	2023762 UM8X26OP- IWD28.0SZ1960G									



Rope Diameter	HYFLEX 8X26 22MM Pi RHOL	HYFLEX 8X26 24MM Pi RHOL	HYFLEX 8X26 26MM Pi RHOL	HYFLEX 8X26 28MM Pi RHOL	HYFLEX 8X26 30MM Pi RHOL	HYFLEX 8X26 32MM Pi RHOL	HYFLEX 8X26 34MM Pi RHOL	HYFLEX 8X26 36MM Pi RHOL	HYFLEX 8X26 38MM Pi RHOL	HYFLEX 8X26 40MM Pi RHOL
30 mm	-	-	-	-	2023763 UM8X260P- IWd30.0SZ1960G	-	-	-	-	-
32 mm	-	-	-	-	-	2023764 UM8X260P- IWd32.0SZ1960G	-	-	-	-
34 mm	-	-	-	-	-	-	2023765 UM8X260P- IWd34.0SZ1960G	-	-	-
36 mm	-	-	-	-	-	-	-	2023766 UM8X260P- IWd36.0SZ1960G	-	-
38 mm	-	-	-	-	-	-	-	-	2023767 UM8X260P- IWd38.0SZ1960G	-
40 mm	-	-	-	-	-	-	-	-	-	2023768 UM8X260P- IWd40.0SZ1960G
42 mm	-	-	-	-	-	-	-	-	-	-
44 mm	-	-	-	-	-	-	-	-	-	-
46 mm	-	-	-	-	-	-	-	-	-	-
48 mm	-	-	-	-	-	-	-	-	-	-
50 mm	-	-	-	-	-	-	-	-	-	-
52 mm	-	-	-	-	-	-	-	-	-	-

Rope Diameter	HYFLEX 8X26 44MM Pi RHOL	HYFLEX 8X26 46MM Pi RHOL	HYFLEX 8X26 48MM Pi RHOL	HYFLEX 8X26 50MM Pi RHOL	HYFLEX 8X26 52MM Pi RHOL
10 mm	-	-	-	-	-
11 mm	-	-	-	-	-
12 mm	-	-	-	-	-
13 mm	-	-	-	-	-
14 mm	-	-	-	-	-
15 mm	-	-	-	-	-
16 mm	-	-	-	-	-
17 mm	-	-	-	-	-
18 mm	-	-	-	-	-
19 mm	-	-	-	-	-



Rope Diameter	HYFLEX 8X26 44MM Pi RHOL	HYFLEX 8X26 46MM Pi RHOL	HYFLEX 8X26 48MM Pi RHOL	HYFLEX 8X26 50MM Pi RHOL	HYFLEX 8X26 52MM Pi RHOL
20 mm	-	-	-	-	-
22 mm	-	-	-	-	-
24 mm	-	-	-	-	-
26 mm	-	-	-	-	-
28 mm	-	-	-	-	-
30 mm	-	-	-	-	-
32 mm	-	-	-	-	-
34 mm	-	-	-	-	-
36 mm	-	-	-	-	-
38 mm	-	-	-	-	-
40 mm	-	-	-	-	-
42 mm	-	-	-	-	-
44 mm	2023770 UM8X26OP-IWd44.OSZ1960G	-	-	-	-
46 mm	-	2023771 UM8X26OP-IWd46.OSZ1960G	-	-	-
48 mm	-	-	2023772 UM8X26OP-IWd48.OSZ1960G	-	-
50 mm	-	-	-	2023773 UM8X26OP-IWd50.OSZ1960G	-
52 mm	-	-	-	-	2023774 UM8X26OP-IWd52.OSZ1960G

- Main Material Steel
- Temperature Range -40° C to + 100° C
- Packaging Unit (PU) Content 1

