

IKAR Kunststoffgehäuse mit verzinktem Stahlseil

Höhensicherungsgerät mit Kunststoffgehäuse und verzinktem Stahlseil



Artikel Name kurz	Länge der Rettungsleine (m) [m]	Auffangurt Verbindung	B [mm]	L [mm]	T [mm]	Nettogewicht kg [kg]
41-HWPS 4,5 51	4.5	IKV 51	130	400	780	2.1
HWPS4.5	4.5	IKV21	130	400	780	2.7
41-HWPS 9 51	9	IKV 51	-	-	-	3.2
41-HWPS 9	9	IKV21	160	455	85	3.7
41-HWPS 18 51	18	IKV 51	220	540	970	6.3
HWPS18	18	IKV 51	220	540	970	6.9
41-HWPS 24 51	24	IKV 51	250	555	970	8.8
HWPS24	24	IKV21	250	557	970	8.4



BESTELLNUMMERN[Global Item Number/Local ERP Number SSCH]

Länge der Rettungsleine (m)	HWPS4.5	HWPS18	HWPS24	41-HWPS 4,5 51	41-HWPS 9	41-HWPS 9 51	41-HWPS 18 51	41-HWPS 24 51
4.5 m	2018861	-	-	2002371 HWPS4,5	-	-	-	-
9 m	-	-	-	-	2018862	2002372 HWPS9	-	-
18 m	-	2018863	-	-	-	-	2002373 HWPS18	-
24 m	-	-	2018864	-	-	-	-	2002374 HWPS24

■ Normen	EN 360: 2002 ANSI Z359.14-2014
■ Farbe	Blau
■ Temperaturbereich	-40°C / +50° C
■ Temperaturbereich	-40°F / +120° F
■ Verpackungseinheit (VPE) Inhalt	1

