

Jeu de levage Power en sangle à 4 brins

Léger et maniable. Souple, imputrescible



Nom court de l'article	Anneau	Élément de crochet	WLL t Angle 0° - 45° [t]	WLL t Angle 45° - 60° [t]	L1 min. [m]	Poids pour 1 m [kg]	Poids par mètre [kg/m]
4 leg LBA 0500 ESHC	MLA-8-10	ESHC-6-10	1.05	0.75	0.7	2.38	1
4 leg LBA 0500 ESLH	MLA-8-10	ESLH-6-10	1.05	0.75	0.7	3.38	1
4 leg LBA 1000 ESHC	MLA-8-10	ESHC-8-10	2.1	1.5	0.9	3.3	0.64
4 leg LBA 1000 ESLH	MLA-8-10	ESLH-8-10	2.1	1.5	0.9	4.3	0.64
4 leg LBA 2000 ESHC	MLA-10-10	ESHC-10-10	4.2	3	0.9	5.9	1.28
4 leg LBA 2000 ESLH	MLA-10-10	ESLH-10-10	4.2	3	0.9	7.75	1.28
4 leg LBA 3000 ESHC	MLA-13-10	ESHC-10-10	6.3	4.5	1.20	10.6	2.2
4 leg LBA 3000 ESLH	MLA-13-10	ESLH-10-10	6.3	4.5	1.20	13.2	2.2

Nom court de l'article	Couleur
4 leg LBA 0500 ESHC	Olive
4 leg LBA 0500 ESLH	Olive
4 leg LBA 1000 ESHC	Violet
4 leg LBA 1000 ESLH	Violet
4 leg LBA 2000 ESHC	Vert
4 leg LBA 2000 ESLH	Vert
4 leg LBA 3000 ESHC	Jaune
4 leg LBA 3000 ESLH	Jaune





NUMÉROS DE COMMANDE[Global Item Number/Local ERP Number SSCH]

Élément de crochet	1.05 t	2.1 t	4.2 t	6.3 t
 ESLH-6-10	2027927 B4-0500-ESLH	-	-	-
 ESHC-6-10	2027923 B4-0500-ESHC	-	-	-
 ESLH-8-10	-	2027928 B4-1000-ESLH	-	-
 ESHC-8-10	-	2027924 B4-1000-ESHC	-	-
 ESLH-10-10	-	-	2027929 B4-2000-ESLH	2027930 B4-3000-ESLH
 ESHC-10-10	-	-	2027925 B4-2000-ESHC	2027926 B4-3000-ESHC

- Normes EN 1492-1: 2000
- Plage de température -40°C / +100°C
- Contenu des unités d'emballage (UE) 1

