



Lashing chain with safety hooks

G100 Lashing chain equipped with safety latch hooks

Item Name short	Chain Diameter	Lashing Capacity [daN]	Chain Component	L1 [m]	Lashing End Fitting Component
Exoset Binding chain load hook LC5000 8mm 2m	8 mm	5000	KLX-8-10	2	CSHC-8-10
Exoset Binding chain load hook LC5000 8mm 3m	8 mm	5000	KLX-8-10	3	CSHC-8-10
Exoset Binding chain load hook LC5000 8mm 4m	8 mm	5000	KLX-8-10	4	CSHC-8-10
Exoset Binding chain load hook LC5000 8mm 5m	8 mm	5000	KLX-8-10	5	CSHC-8-10
Exoset Binding chain load hook LC8000 10mm 2m	10 mm	8000	KLX-10-10	2	CSHC-10-10
Exoset Binding chain load hook LC8000 10mm 3m	10 mm	8000	KLX-10-10	3	CSHC-10-10
Exoset Binding chain load hook LC8000 10mm 4m	10 mm	8000	KLX-10-10	4	CSHC-10-10
Exoset Binding chain load hook LC8000 10mm 5m	10 mm	8000	KLX-10-10	5	CSHC-10-10
Exoset Binding chain load hook LC13400 13mm 2m	13 mm	13400	KLX-13-10	2	CSHC-13-10
Exoset Binding chain load hook LC13400 13mm 3m	13 mm	13400	KLX-13-10	3	CSHC-13-10
Exoset Binding chain load hook LC13400 13mm 4m	13 mm	13400	KLX-13-10	4	CSHC-13-10
Exoset Binding chain load hook LC13400 13mm 5m	13 mm	13400	KLX-13-10	5	CSHC-13-10

ORDER NUMBERS[Global Item Number/Local ERP Number SSUK]

Dimension L1	8 mm	10 mm	13 mm
2 m	2020057 2020057	2020061 2020061	2020065 2020065
3 m	2020058 2020058	2020062 2020062	2020066 2020066
4 m	2020059 2020059	2020063 2020063	2020067 2020067
5 m	2020060 2020060	2020064 2020064	2020068 2020068

■ Norms

EN 12195-3

SpanSet (UK) Limited
Telford Way
Middlewich Cheshire
CW10 0HX United
Kingdom
+44 (0) 1606 737494
info@spanset.co.uk
www.spanset.co.uk



Subject to technical changes. All rights reserved. No part of this Technical Data Sheet may be reproduced in any form (print, photocopy, microfilm or any other process) or processed, duplicated or distributed using electronic systems without the written permission of SpanSet. This Technical Data Sheet has been prepared with due care; SpanSet accepts no liability for errors or omissions. © SpanSet (UK) Limited - United Kingdom

**SpanSet
Certified
Safety**

■ Grade	100
■ Main Material	Steel
■ Colour	Blue
■ Temperature Range	-30° C to + 100° C
■ Packaging Unit (PU) Content	1

