




Laufkatze ohne Antrieb

Zuverlässige und robuste, schubfreie Lenkung mit Öse

Artikel Name kurz	Breite des Strahls [mm]	WLL [kg]	WLL [t]	A [mm]	B [mm]	C [mm]	D [mm]
LK5000A	50 - 220	500	5	225	324	88	16
LK10000A	58 - 220	1000	1	252	334	103	17
LK20000A	66 - 220	2000	2	300	342	127	21
LK30000A	74 - 220	3000	3	360	358	177	21
LK50000A	90 - 220	5000	5	400	372	192	31



Artikel Name kurz	E [mm]	F [mm]	G [mm]	H [mm]	I [mm]	Nettogewicht kg [kg]
LK5000A	25	16	27	62	15	8.5
LK10000A	30	17	30	62	15	10.5
LK20000A	40	18	38	80	18	18
LK30000A	48	18	45	97	15	32
LK50000A	58	23	52	110	20	48.5

BESTELLNUMMERN[Global Item Number/Local ERP Number SSCH]

WLL	LK5000A	LK10000A	LK20000A	LK30000A	LK50000A
500 kg	2009523 LK5000A	-	-	-	-
1000 kg	-	2009524 LK10000A	-	-	-
2000 kg	-	-	2009525 LK20000A	-	-
3000 kg	-	-	-	2009526 LK30000A	-
5000 kg	-	-	-	-	2009527 LK50000A

■ Verpackungseinheit (VPE) Inhalt 1

