

Magnum-X

Die neue Dimension in der Hebetechnik



Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	ca. Auflagebreite unter Last in mm [mm]	ca. Auflagedicke unter Last in mm [mm]	Nettogewicht kg [kg]
Magnum-X 5t 2m	5000	5	2	1.0	36	6	0.94
Magnum-X 5t 3m	5000	5	3	1.0	36	6	1.41
Magnum-X 5t 4m	5000	5	4	1.0	36	6	1.88
Magnum-X 5t 5m	5000	5	5	1.0	36	6	2.35
Magnum-X 5t 6m	5000	5	6	1.0	36	6	2.82
Magnum-X 5t 7m	5000	5	7	1.0	36	6	3.29
Magnum-X 5t 8m	5000	5	8	1.0	36	6	3.76
Magnum-X 10t 4m	10000	10	4	2	67	11	4.1
Magnum-X 10t 5m	10000	10	5	2	67	11	5
Magnum-X 10t 6m	10000	10	6	2	67	11	5.9
Magnum-X 10t 7m	10000	10	7	2	67	11	6.8
Magnum-X 10t 8m	10000	10	8	2	67	11	7.7
Magnum-X 10t 10m	10000	10	10	2	67	11	9.5
Magnum-X 10t 12m	10000	10	12	2	67	11	10.8
Magnum-X 20t 4m	20000	20	4	2	88	13	7.7
Magnum-X 20t 5m	20000	20	5	2	88	13	9.5
Magnum-X 20t 6m	20000	20	6	2	88	13	11.3
Magnum-X 20t 7m	20000	20	7	2	88	13	13.1
Magnum-X 20t 8m	20000	20	8	2	88	13	14.9



Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	ca. Auflagebreite unter Last in mm [mm]	ca. Auflagedicke unter Last in mm [mm]	Nettogewicht kg [kg]
Magnum-X 20t 10m	20000	20	10	2	88	13	18.5
Magnum-X 20t 12m	20000	20	12	2	88	13	21.6
Magnum-X 30t 4m	30000	30	4	2	91	23	12.1
Magnum-X 30t 5m	30000	30	5	2	91	23	15
Magnum-X 30t 6m	30000	30	6	2	91	23	17.9
Magnum-X 30t 7m	30000	30	7	2	91	23	20.8
Magnum-X 30t 8m	30000	30	8	2	91	23	23.7
Magnum-X 30t 10m	30000	30	10	2	91	23	29.5
Magnum-X 30t 12m	30000	30	12	2	91	23	27.6
Magnum-X 40t 4m	40000	40	4	2	101	25	16.1
Magnum-X 40t 5m	40000	40	5	2	101	25	20
Magnum-X 40t 6m	40000	40	6	2	101	25	23.9
Magnum-X 40t 7m	40000	40	7	2	101	25	27.8
Magnum-X 40t 8m	40000	40	8	2	101	25	31.7
Magnum-X 40t 10m	40000	40	10	2	101	25	39.5
Magnum-X 40t 12m	40000	40	12	2	101	25	42
Magnum-X 50t 4m	50000	50	4	2	143	24	21.3
Magnum-X 50t 5m	50000	50	5	2	143	24	26.5
Magnum-X 50t 6m	50000	50	6	2	143	24	31.7
Magnum-X 50t 7m	50000	50	7	2	143	24	36.9



Artikel Name kurz	WLL [kg]	WLL [t]	L1 [m]	L1 min. [m]	ca. Auflagebreite unter Last in mm [mm]	ca. Auflagedicke unter Last in mm [mm]	Nettogewicht kg [kg]
Magnum-X 50t 8m	50000	50	8	2	143	24	42.1
Magnum-X 50t 10m	50000	50	10	2	143	24	52.5
Magnum-X 50t 12m	50000	50	12	2	143	24	62.4
Magnum-X 60t 4m	60000	60	4	3	142	26	28.9
Magnum-X 60t 5m	60000	60	5	3	142	26	36
Magnum-X 60t 6m	60000	60	6	3	142	26	43.1
Magnum-X 60t 7m	60000	60	7	3	142	26	50.2
Magnum-X 60t 8m	60000	60	8	3	142	26	57.3
Magnum-X 60t 10m	60000	60	10	3	142	26	71.5
Magnum-X 60t 12m	60000	60	12	3	142	26	69.6

Artikel Name kurz	Gewicht pro Meter [kg/m]	Farbe
Magnum-X 5t 2m	0.47	Rot
Magnum-X 5t 3m	0.47	Rot
Magnum-X 5t 4m	0.47	Rot
Magnum-X 5t 5m	0.47	Rot
Magnum-X 5t 6m	0.47	Rot
Magnum-X 5t 7m	0.47	Rot
Magnum-X 5t 8m	0.47	Rot
Magnum-X 10t 4m	0.93	Orange
Magnum-X 10t 5m	0.93	Orange
Magnum-X 10t 6m	0.93	Orange
Magnum-X 10t 7m	0.93	Orange



Artikel Name kurz	Gewicht pro Meter [kg/m]	Farbe
Magnum-X 10t 8m	0.93	Orange
Magnum-X 10t 10m	0.93	Orange
Magnum-X 10t 12m	0.93	Orange
Magnum-X 20t 4m	2.05	Orange
Magnum-X 20t 5m	2.05	Orange
Magnum-X 20t 6m	2.05	Orange
Magnum-X 20t 7m	2.05	Orange
Magnum-X 20t 8m	2.05	Orange
Magnum-X 20t 10m	2.05	Orange
Magnum-X 20t 12m	2.05	Orange
Magnum-X 30t 4m	3.27	Orange
Magnum-X 30t 5m	3.27	Orange
Magnum-X 30t 6m	3.27	Orange
Magnum-X 30t 7m	3.27	Orange
Magnum-X 30t 8m	3.27	Orange
Magnum-X 30t 10m	3.27	Orange
Magnum-X 30t 12m	3.27	Orange
Magnum-X 40t 4m	3.5	Orange
Magnum-X 40t 5m	3.5	Orange
Magnum-X 40t 6m	3.5	Orange
Magnum-X 40t 7m	3.5	Orange
Magnum-X 40t 8m	3.5	Orange
Magnum-X 40t 10m	3.5	Orange
Magnum-X 40t 12m	3.5	Orange
Magnum-X 50t 4m	4.83	Orange
Magnum-X 50t 5m	4.83	Orange



Artikel Name kurz	Gewicht pro Meter [kg/m]	Farbe
Magnum-X 50t 6m	4.83	Orange
Magnum-X 50t 7m	4.83	Orange
Magnum-X 50t 8m	4.83	Orange
Magnum-X 50t 10m	4.83	Orange
Magnum-X 50t 12m	4.83	Orange
Magnum-X 60t 4m	5.83	Orange
Magnum-X 60t 5m	5.83	Orange
Magnum-X 60t 6m	5.83	Orange
Magnum-X 60t 7m	5.83	Orange
Magnum-X 60t 8m	5.83	Orange
Magnum-X 60t 10m	5.83	Orange
Magnum-X 60t 12m	5.83	Orange

BESTELLNUMMERN[Global Item Number/Local ERP Number SSCH]

Länge L1	5000 kg	10000 kg	20000 kg	30000 kg	40000 kg	50000 kg	60000 kg
2 m	2025045 ESX050/0200	-	-	-	-	-	-
3 m	2026602 ESX050/0300	-	-	-	-	-	-
4 m	2010959 ESX050/0400	2002763 ESX100/0400	2002765 ESX200/0400	2002769 ESX300/0400	2002771 ESX400/0400	2002773 ESX500/0400	2002775 ESX600/0400
5 m	2010960 ESX050/0500	2002764 ESX100/0500	2002766 ESX200/0500	2002770 ESX300/0500	2002772 ESX400/0500	2002774 ESX500/0500	2002776 ESX600/0500
6 m	2010961 ESX050/0600	2003251 ESX100/0600	2003253 ESX200/0600	2003257 ESX300/0600	2003259 ESX400/0600	2003261 ESX500/0600	2003263 ESX600/0600
7 m	2010962 ESX050/0700	2003252 ESX100/0700	2003254 ESX200/0700	2003258 ESX300/0700	2003260 ESX400/0700	2003262 ESX500/0700	2003264 ESX600/0700
8 m	2010963 ESX050/0800	2003738 ESX100/0800	2003739 ESX200/0800	2003741 ESX300/0800	2003742 ESX400/0800	2003743 ESX500/0800	2003744 ESX600/0800
10 m	-	2014760 ESX100/1000	2014762 ESX200/1000	2014765 ESX300/1000	2014767 ESX400/1000	2014769 ESX500/1000	2014771 ESX600/1000
12 m	-	2014761 ESX100/1200	2014763 ESX200/1200	2014766 ESX300/1200	2014768 ESX400/1200	2014770 ESX500/1200	2014772 ESX600/1200



■ Normen	EN 1492-2: 2000
■ Hauptmaterial	Hochleistungspolyester
■ Temperaturbereich	- 40 tot + 100°C
■ Etikettenschutz	Ja
■ Verpackungseinheit (VPE) Inhalt	1

1. WLL - working load limit, nominal load capacity. Applies to direct attachment type.
2. L1 - working length
3. Deviating from DIN EN 1492-2, the material in this round sling is suitable up to an operating temperature of +70°C.
4. In DIN EN 1492-2, HMPE is not listed as a material and material mixtures are not provided for.

